

A

- Abrupt
 - contraction, 234, 626
 - expansion, 224, 230, 626
- Acceleration, 191
 - pressure losses of, 585
- Acetone, density of, 10t
- Aerodynamic
 - characteristics, 297
 - effect, 314
 - grid, 411
 - losses, 187
- Aerodynamics, 1
- Air conduit
 - flexible, 108
 - glass-fabric, 108, 419
- Air distributors, with perforated outlet, 758–763t
- Air heater, 834t, 835t
 - electric, 836t, 837t
 - smooth-tube, 836t
- Air intakes, 188
- Air pipelines, asperities in, 107
- Air-intake devices, 214t, 215t
- Ammonia, density of, 10t
- Angle of twisting, 327
- Aniline, density of, 10t
- Annular
 - grooves, 105
 - jet, 312
 - step, 492
 - turn, 417
- Aperture in the wall, 239
- Apparatus, various types of, 779
- Approach velocities, 587
- Area ratio, 287, 321
- Aspect ratio, 51
- Asperities, 86, 402
 - local, 404
- Asymmetric velocity distribution, 228
- Attenuation, 625
- Automatic control, 621
- Axial turbomachines, 325

B

- Badly streamlined bodies, 677t, 678t
- Badly streamlined body of revolution, 675
- Baffle, 179, 244, 315
- Baffle plate, 103
- Bag filters, 622
- Bars, 578
- Beds, 575
- Bend, 391, 424–426t, 431t, 789t
 - combined (joint), 407
 - expanding, 394
 - flexible glass-cloth, with furrowed surfaces, 462t, 463t
 - joined, gate-like, 455t
 - joined, S-shaped, spatial (flow into two mutually perpendicular planes), 451t, 452t
 - joined, U-shaped, in one plane, 453t, 454t
 - smooth, 409
 - Z-shaped, 408

Note. Page numbers followed by the letter t denote tables; and numbers followed by n denote footnotes.

- Bend-collector, combination, mutual effect of, 855t
 - Bend-wye, combination, mutual effect of, 852–854t
 - Benzene, density of, 10t
 - Bernoulli equation, 25, 29, 301
 - Beveling, 394
 - Blading, 327
 - Blasius formula, 88
 - Blowing intensity, 188
 - Blowoff, 310
 - Bodies
 - of different shapes, three-dimensional flow, 693–695t
 - of irregular shape, 607–609t
 - of isomeric shape, three-dimensional flow, 692t
 - Body midsection, 674
 - Bottom guides, 621
 - Boundary layer, 20, 288
 - fully turbulent, 291
 - separation of, 291
 - suction, 308, 309
 - thin, 85
 - Branch
 - gooseneck-type, 407
 - lateral, 67
 - paired, 408
 - side, 486, 500
 - smoothly rounded, 491
 - Bromine, density of, 10t
 - Bundle
 - of smooth-wall in-line tubes (in cross-flow), 838t, 839t
 - of smooth-wall staggered tubes (in cross-flow), 837, 838t
 - Buoyancy, 38
 - negative, 64
 - Butane (normal), density of, 10t
 - Bypasses, 391, 626
 - sharply curved, of rectangular cross section, 458t, 459t
- C**
- Carbonic acid, 107
 - Castor oil, density of, 10t
 - Center of gravity, 53
 - Centrifugal forces, 392
 - Chamber end, 624
 - Channel
 - common, 484
 - magnetohydrodynamic, 50
 - narrow, 180
 - narrow annular, 99
 - plane, 227
 - rectangular, 96
 - rotating, 802
 - sharply bent, 408
 - square, 96
 - stepwise, 232
 - straight, 707
 - vertical, 423
 - Channel entry
 - through a fixed louver, 212t
 - through perforated plates, 213t
 - Characteristic
 - dimension, 52
 - length, 85
 - Chords, arranged crosswise, 611t
 - Circular-annular entry, 186
 - Circular
 - bellmouth, 181
 - collector, 186, 187
 - cylinders, bundles of, 102
 - plates, in a tube, three-dimensional flow, 697t
 - section, bends and elbows, 429–431t
 - sector, 100
 - Circular-section rods, 591
 - Circumferential velocity, 802
 - Coal tar, density of, 10t
 - Coconut oil, density of, 10t
 - Coefficient
 - of hydraulic friction, 405
 - of radial nonuniformity, 323
 - Collector, 178n
 - Combined suction, 310
 - Complex
 - fitting, 626
 - geometry, 95
 - parts, 626
 - Compressibility, 288

- Compressible
 - fluids, 25
 - gas, discharge of, 63
 - Compressor, 323, 329
 - stages, 187
 - Concrete pipelines, 105
 - cavities, 105
 - irregularities, 105
 - Configuration
 - in-line, 576, 795
 - staggered, 577, 795
 - staggered, of orifices, 577
 - Constant flow conditions, 278
 - Constant-mass core, 624
 - Container, long passive, 130
 - Containers
 - finite-length, 128
 - passive cylindrical, 126
 - self-propelled, 126
 - Continuity
 - equation, 24, 301
 - of a stream, 24
 - Contraction, 581
 - angle, 332
 - Controlling devices, 617, 618
 - Coriolis
 - coefficients, 29
 - forces, 803
 - Corner
 - beveled, 413
 - inner, 410
 - outer, 410
 - Corrosion, 87
 - Corrugated strips, 581
 - Couette flow, 127
 - annular forced, 128
 - Counterflow, 584
 - Coupled joints, 105
 - Critical
 - Reynolds number, 20
 - zone, 136t, 137t
 - Cross section
 - elliptical, 244
 - expansion of, 298
 - of fittings, 4
 - rectangular, 397, 421
 - variable, 332
 - Crosses
 - inflow (converging), 496
 - standard, 497
 - straight, diverging, 563–565t
 - Crosswise bundles, 575
 - Cyclone, 780, 808–810t, 812–814t
 - battery, 815t
 - countercurrent, 811t
 - diameter of, 782
 - direct-flow, 816t, 817t
 - Cylinders, 666
 - circular rough, in a tube, plane-parallel flow, 682t
 - circular smooth, in a tube, plane-parallel flow, 680t, 681t
 - elliptical smooth or ellipsoid, in a tube, three-dimensional flow, 696t
 - layered (porous), 586
 - loosely arranged, 103
 - pair of circular, in a tube, plane-parallel flow, 688t
 - single circular, with fins or laths in a tube, plane-parallel flow, 683t
 - smooth, in a tube, arranged in one central longitudinal row, plane-parallel flow, 699t
 - Cylindrical
 - (spherical) barriers, 666
 - layer, 586
- D**
- Dean number, 398
 - Deflectors, 805, 846t, 847t
 - Deformation, 333
 - Dichloroethane, density of, 10t
 - Diffuser, 225
 - annular with inner fairing, 370t, 371t
 - annular, 709
 - axial-annular, 323
 - axial-inlet radial-annular, 709
 - axisymmetric, 295, 296
 - conical, 280, 338–344t
 - conical, at large subsonic velocities, 345–349t
 - conventional, 332

- curved-axis, 330, 331
- divergence angle, 788n
- exit, 708
- flow patterns in, 278
- in a network, 277
- jet, 312
- of circular cross section, 358t, 359t
- of circular cross section, with curved axis, 374t
- of circular cross section, with expansion
 - in two planes, 790t
- of circular cross section, with stepped walls, 360–362t
- of rectangular cross section, 350–352t
- of rectangular cross section, installed downstream, 369t
- of rectangular cross section, with stepped walls, 362t, 363t
- of reduced resistance, 365t, 366t
- of reduced resistance, with a screen, 365t
- optimum characteristics of, 303t
- plane, 226, 283, 289, 300, 318, 790t
- plane, five-channel subsonic, 358t
- plane stepped, 321
- preseparation, 296
- pyramidal, 300, 709
- radial-annular, 709
- rectangular, 289
- rectilinear, 307, 318
- separation-free, 284
- short, 308
- step, 231
- stepped, 323
- stepwise, 314
- surface, highly polished, 708
- turbomachinery, 372t
- with asymmetric expansion in one plane,
 - installed downstream, 367t, 368t
- with curvilinear boundaries, 359t, 360t
- with expansion in one plane, 353–355t
- with expansion in one plane, with curved axis, 373t
- with expansion in one plane, with stepped walls, 364t
- with stepped walls, installed downstream, 369t
 - with symmetric expansion in one plane,
 - installed downstream, 367t
 - with transition from a circle into a rectangle, 381t
- Dimensionless velocities, 412
- Dimples, 800
- Discharge, 243
 - coefficient, 55–57, 190
 - coefficient, values of, 58–62t
 - corona, 791
 - diffusers, downstream of axial fans, 753t
 - from a bend and a composite elbow, 757t
 - from a diffuser (with a smooth rounded inlet),
 - onto a baffle, 743t
 - from a straight channel, through a fixed louver grating, 771t
 - from a straight tube, through an orifice
 - or perforated plate, 767–769t
 - from a straight walled elbow, 754–756t
 - from a tube (channel) onto a baffle, 742t
 - from a tube made flush, with the wall
 - in the presence of a passing stream, 721t
 - from a tube, through an orifice or perforated plate, in transition and laminar regions, 769t
 - sections under different conditions, 772t
 - side, from the end orifice, of a circular pipe, 770t
 - velocity, 63
- Discharging collector, 112
- Disk throttle, 619
- Dispersed dust, 585
- Divergence angle, 227, 279, 286, 289, 322
 - fictitious, 316
 - large, 707
 - limiting, 277
 - moderate, 288
 - small, 306, 707
- Doubly curved turns at different values, 450t, 451t
- Drag coefficient, 663
- Driving head
 - negative, 40
 - net (self-draught), 38
- Dry filtration, 585
- Dry gas
 - density of, 11t

specific heats, 11t
 Dust
 catcher, 786
 content, 585
 Dust separator
 battery-type, 783
 louver-type, 779
 Dust-laden air flow, 116
 Dust-trapper, 820t
 with perforated plates, 821t
 Dynamic pressure losses, 42

E

Eddy
 extensive, 401
 formation, 42, 617
 internal motion, 48
 Edges
 beveled, 236, 712
 inlet, 177
 rounded, 182, 712
 sharp, 182
 thick, 236
 thickened, 182
 Efficiency, 330
 coefficient, 302
 Ejector mixing chamber, 228
 Elbows, 391, 789t
 combined, 409
 composed of separate elements, 438t
 joined, made from zinc-coated sheet, 459–461t
 of circular cross section, with profiled guide
 vanes, 468t
 of rectangular cross section, with different
 shapes, 436t, 437t
 of rectangular cross section, with thin guide
 vanes, 466t
 pressure profiles, 392
 right-angle, 394, 409
 rounding of, 393
 segmented, of circular cross section, 439–441t
 smooth, of rectangular cross section, with thin
 guide vanes, 467t
 U-shaped, rectangular cross section, 449t

velocity profiles, 392
 with rounded and diverging or converging exit,
 434t
 with rounded corners, 435t
 with sharp corners, 432t, 433t
 Z-shaped, with rounded corners, 445t
 Z-shaped, with sharp corners, 442–444t
 Π-shaped, 408
 Π-shaped, with rounded corners, 448t
 Π-shaped, with sharp corners, 446t, 447t
 Electric field length, 792
 Electrical conductivity, 50
 Electromagnetic fields, 49
 Element shape, 44
 Elements, adjacent, 45
 Ellipse semiaxes, 245
 Emery paper, 402
 End-face wall, 179
 Energy
 equation (see Bernoulli equation)
 internal, 30
 kinetic, 277
 losses, 191
 potential, 277
 Equivalent angles, 318
 Excavation, 675
 Exhaust vents
 circular, 764t
 of rectangular cross section, lateral openings
 with fixed louvers, 765t, 766t
 of rectangular cross section, lateral openings
 without fixed louvers, 765t, 766t
 straight, 764t
 Expansion
 joints, types of, 659t, 660t
 losses, 298
 Expansions, 581

F

Fabrics, 575
 Fairings, 626
 Fan
 axial, inlet elements of, 216t
 blades bent backward, 217t

- blades bent forward, 218t
- centrifugal, 709
- centrifugal, inlet elements of, 217t
- rotor, 67
- shaft, 80
- Filters
 - aerosol, 787
 - bag, 786, 824t
 - electrostatic air, 830t, 831t
 - electrostatic, 828t
 - exhaust, 779
 - frame, 826t
 - industrial electrostatic, 829t
 - laboratory, 827t
 - modular unified, 822t, 823t
 - roll, 824–826t
- Filtering
 - cloth, 585
 - fabrics (according to Adamov), 612t
 - materials, at high pressures of the flow
 - medium (clean), 601t, 602t
- Filtration rate limits, 787
- Fins, 799
 - lateral, 319
 - spiral, 99
- Fixed louver, 185, 186, 713
- Flap (in the system), 644t
- Flat plate, 670
- Flow
 - adiabatic, 102
 - at the exit from tubes and channels, 705
 - axisymmetrical, 589
 - boundary layer, 101
 - cavitation-free, 421, 679
 - central impingement of, 792
 - deflection, 322
 - distribution, nonuniform, 28
 - dust-laden, 420
 - incoming, 243
 - initial nonuniformity of, 290, 293
 - internal, 49
 - lateral impingement of, 792
 - lateral incidence of, 792
 - mean velocity, 23
 - moderate nonuniformity, 28
 - nonisothermal, 51
 - nonseparating, 278, 289
 - nonstabilized, 100
 - obstacle, 664
 - of stagnated gas, 32
 - of subsonic fluid, 288
 - of suspensions, 52
 - oscillating, 666
 - past obstructions in a tube, 663
 - past two cylinders, 673
 - peripheral impingement of, 792
 - peripheral incidence of, 791
 - plane-parallel, 50
 - pulsations, 312
 - secondary, 95
 - separationless models of, 310
 - stabilized, 19, 89
 - stabilized laminar, 93
 - stabilized turbulent, 665
 - stratified, 589
 - supply, methods of, 793
 - swirled, 327
 - three-dimensional, 664
 - through barriers uniformly distributed over
 - the channel cross section, 575
 - through labyrinth seals, 617
 - through pipe fittings, 617
 - turbulent stabilized, 93
 - twisted, 800
 - twisting, 327
 - volumetric, 45
- Flowing medium, density of, 9, 41
- Flow rate equation, 23
- Flow regime, 4, 44
 - fluid, 18
 - laminar, 19
 - of mass, 23
 - stepwise increase in, 118
 - volumetric, 24
- Flow separation, 21, 191, 302, 318, 400, 403
 - fully developed, 278
 - in diffusers, 282
 - inception of, 278
 - nondeveloped, 278
- Flow spreading, 707

- Flow streams
 - division into, 483
 - merging of, 483
 - Flow-stopping devices, 617
 - Fluid
 - calculation of resistance, 67
 - compressibility of, 401
 - conducting, 50
 - friction loss, 41
 - low-viscous, 52
 - motion, equations of, 23
 - overall resistance, 44
 - real (viscous), 18
 - transport capacity, 106
 - Fluoroplastic, 109
 - Flute layer, 404
 - Foam, 786
 - Forced ventilation, 67
 - Forced ventilation system, calculation
 - of resistance, elements of the system, 68–71t
 - Fouling, 581
 - Free discharge, 706, 707
 - from a circular straight wall diffuser, 722–724t
 - from a rectilinear (straight wall) diffuser, of
 - rectangular (square) cross section, 735–738t
 - from a straight tube, at different velocity
 - distributions, 719t, 720t
 - from a straight wall plane (rectangular) diffuser, 739–741t
 - from annular diffusers, 744t, 745t
 - from axial-annular-radial diffusers, 746t, 747t
 - from conical diffusers, at high subsonic
 - velocities, 725–734t
 - from rectangular diffusers, downstream
 - of a centrifugal induced draft fan, 748t
 - nonsymmetrical diffuser, downstream
 - of a centrifugal intake fan, 749t
 - pyramidal diffuser, downstream of a centrifugal
 - intake fan, 750t
 - Free-area coefficient, 578
 - Frequency of vibrations, 679
 - Friction coefficient, 2, 49, 85
 - diagrams of, 133–162t
 - during acceleration, 119
 - during retardation, 119
 - Friction losses, 37, 298
 - Frictional drag, 41
- G**
- Gap, 625
 - Gas
 - at high pressures in atmosphere, 63
 - cleaning, 72
 - density of, 10t
 - dynamic viscosity of, 14t
 - equilibrium of, 21
 - fittings, 406
 - kinematic viscosity of, 15t
 - mains, 72
 - multicomponent, 10
 - perfect, 24
 - perfectly stagnated, 33
 - pipe fittings, 406
 - pipelines, 106
 - properties, 9
 - Gasdynamic functions for subsonic flow, 34t
 - Gas–liquid mixture, 53, 423
 - Gate valves
 - in a straight tube, 631t, 632t
 - plane-parallel, of the Ludlow type, 633–635t
 - sector, 643t, 644t
 - Gates
 - circular outlet seal, 637t, 638t
 - conical, revolving, 639t
 - disk seal, 620
 - rolling seal, 636t
 - spherical seal, with a spherical valve disk
 - and seat, 642t
 - spherical seal, with one-sided sealing of
 - the valve, 640t
 - spherical seal, with two-sided sealing
 - of the valve, 641t
 - Globe valve
 - "Kosva" angle, at complete opening, 628t
 - direct-flow angle, 629t
 - standard, with dividing walls at complete
 - opening, 630t
 - Glycerine (anhydrous), density of, 10t
 - Grating, 580

fixed louver, 185
 in a wall infinite surface area, 272t
 made from bars with the angle of attack, 602t, 603t
 made of bars with the angle of attack, 603t, 604t
 standard, 185, 713
 with adjustable louvers, 272t
 Grid, 575
 at subsonic flow velocities, 599t, 600t
 made of thickened laths, 594t
 nonuniform, 588
 perforated, 576
 thickened, 580
 thin-walled, 592t
 with beveled orifice, 593t
 with different shapes of orifice edges, 597t
 with rounded orifice edges, 595t, 596t
 Guide vanes, 315, 317

H

Hagen–Poiseuille
 curve, 101
 law, 92
 Hartman number, 50
 Headers, 498
 (diverging) box, 566t
 intake, 568t
 outlet, 567t
 Z-shaped, 570t
 Π-shaped, 569t
 Heat exchangers, 794
 multipass, 800
 of various types, 843t
 Heat transfer, 116
 Heaters, 795
 Heating (cooling) surface, 798
 Heating furnace, 845t
 Heterogeneous (nonuniform) systems, 49
 Heterogeneous systems, resistance for, 48
 High resistance, network of, 46
 Homogeneous systems, resistance for, 48
 Hood, 191
 Hoses
 characteristics of, 154t

reinforced rubber, 108, 109
 smooth rubber, 108
 stabilized flow in various types, 154–156t

Hydraulic

diameter, 50
 resistance, 1, 86
 resistance of networks, 41

Hydraulics, 1

Hydrodynamic similarity, 50

Hydrogen sulfide, 107

I

Inclination angle, 798

Incompressible homogeneous medium, 25

Incompressible fluid, 25, 109

flow of, 53
 jet of, 37

Inertial separation, 786

Injection, 115

Inlets

beveled wall, 177
 circular bellmouth, 196–198t
 entry from a limited volume, 200t
 pipes of axial stationary turbo-machines, 213t
 pipes, 187
 resistance coefficients of, 177
 side, 183
 with different types of mounting, 201t, 202t
 with facing baffle, 200t
 with straight boundaries, 178

Insert, 407

Intake collector, 499n

Interaction effect, 623

Interconnected bodies, 675

Invariability of density, 43

Inverse problem, 296

Irregular shape, 582

Irreversible losses, 331

Irrotational (laminar) motion, 48

Isentropic process, 47

Isentropic retardation, 33

Isotherm, 31

J

Jet

- additional expansion of, 708
- axisymmetric free submerged, 715–717t
- discharge, 53
- discharged, 705
- expansion, 53
- free, 229, 625, 714
- free, of circular cross section, 773t, 774t
- free, plane-parallel, 775t, 776t
- ideal gas, 33
- narrow flow, 588

K

- Kerosene, density of, 10t

L

- Labyrinth, 624
 - with flow passage from one volume, 657–659t
- Labyrinth seal
 - with an enlarged gap, 655t, 656t
- Laminar regime, 145t
- Lateral entrance, 183
- Light machine oil, density of, 10t
- Lignite oil, density of, 10t
- Limiting cavitation numbers, 420
- Linear frictional resistance, 2n
- Linseed oil (boiled), density of, 10t
- Liquids
 - equilibrium of, 21
 - incompressible, 38
 - properties of, 9
- Local
 - losses, 298
 - pressure drops, 2
 - resistance, 41
 - shear stress, 96
 - stalls, 402
- Locking devices, 47, 806
- Longitudinal
 - oscillating velocity, 669
 - rows, 673
- Loose material, 575

- Lumped material, 575
- Lumps of spherical or irregular shape, 582

M

- Mach number, 4, 31, 44, 576
 - high, 242, 266t
- Magnetohydrodynamic (MHD) channel, 50
- Mass discharge, 63
- Mass flux, 35
 - reduced density of, 35
- Mean flow velocity, 23
- Mechanical contamination, 106
- Media
 - cemented or bonded, 581
 - loose or unbonded, 581
- Meshes, 581
- Metallic strips, 108
- Mixing chamber, 229
- Moisture, 107
- Momentum exchange, 400
- Movable flaps, 270–272t

N

- Navier–Stokes equations, 129
- Newton's binomial rule, 37
- Newtonian fluid, 48
- Nikuradse's resistance equations, 89
- Nitrogen dioxide, density of, 10t
- Nonuniformity, 41
- Notches, 97
- Nozzle, 53, 56
 - bellmouth, 266t, 267t
 - converging conical, 198t
 - converging, 331, 332
 - converging, of circular cross section, 375–377t
 - inner cylindrical, 57
 - losses, 63
 - shape of, 58–62t
- Numerical methods, 289

O

- Oblique
 - flow, 189
 - inflow, 190

Oblong body, 665
 Optimal geometric parameters, 418
 Optimization parameters, 187
 Orifices
 change in flow area of, 223
 change in velocity of, 223
 discharge from, 54
 gas flow through, 53
 grid, 181
 in a straight tube, 259–262t
 in a thin wall in presence of a passing flow, 267–270t
 in a wall with infinite surface area, 263t, 264t
 in transient and laminar regions, 264t, 265t
 in tubes at large subsonic velocities, 266t
 liquid flow through, 53
 round-edged, 239
 shape of, 58–62t
 sharp-edged, 236, 238, 241n
 side, 184
 single, 181
 submerged, 54
 types installed in a transition section, 256–258t
 Oscillations, 416
 Outlet elements, installed downstream
 of centrifugal fans, 751t, 752t
 Oxygen, 107

P

Packed bed, 582
 Packings, 575
 a bed of spherical or lumpy irregular-shape bodies, 605t, 606t
 chordlike, 581, 584
 density of, 787
 gridlike, 581
 of ceramic Raschig rings, 610t
 of wooden laths (chordlike), 611t
 wetted, 584
 Paired collectors, 115
 Parabolic
 stagnant zone, 667
 velocity profile, 226
 Particles
 binding of, 786

 capture of, 783
 macroscopic, 115
 nonsphericity of, 671
 of irregular shape (see Bodies of irregular shape)
 suspended, 779
 Passing stream, 243
 Pasted strip, 404
 Perforated plates, 227, 237, 575
 in tubes at large subsonic velocities, 266t
 series of, 792
 wetted, 785
 Perforated
 surfaces, 710
 walls, 110
 Permeability, 586
 Perturbations, 88
 Physical quantities, 4
 names and dimensions of, 5–8t
 Pipe
 annular, 19
 bent, 51
 corroded steel, 72
 exhaust, 782
 exit section of, 2
 fittings, 806
 inlet, 187
 short, 2
 smooth, 4
 Pipeline, 590
 formation of deposits in, 106
 Pitch
 nonuniform transverse, 797
 variable, 797
 Plugs, 618
 cone, 623
 Plunger stroke, 620
 Pneumatic transport, 419
 Point of transition, 669
 Poiseuille flow, 127
 Polluted air, 805
 Polymers, 109, 115
 Polypropylene, 109
 Polytropic exponent, 30
 Poorly streamlined bodies, 669

Pores, 581
 Porous materials, 578
 bounded, 583
 Porous
 medium, 581
 segment, 111
 Positive pressure gradient, 189
 Postcritical region, 286
 Poster stamped paper, 402
 Prandtl formula, 87
 Preinserted cylindrical segment, 293
 Preseparated layer, 319
 Pressure-boosting device, 64
 Pressure
 heads, 27
 recovery coefficient, 233
 reduction coefficient, 707
 reduction factors, 725–734t
 systems, 1
 units, 30
 acceleration (deceleration) losses, 798
 calculation of distribution, 47
 elevation, 40
 excess, 40
 redistribution of, 51
 small drop, 38
 static, 28
 total, 40
 Prismatic bodies, 669
 Process apparatus, 579
 Profile, of symmetrical velocity, 289
 Profiled preseparation, 319
 Profiles
 rolled and shaped, in a tube, plane parallel
 flow, 688t, 689t
 shaped, placed in one longitudinal row,
 in a tube, plane-parallel flow, 698t
 Protuberances, 86
 Pulverized material, 419, 420
 Pumps, 329

Q

Quadratic region, 619

R

Radiators
 finned tubular, 832t, 833t
 honeycomb, 794
 honeycomb, with hexagonal or circular pipes,
 831t, 832t
 plate, 833t
 tube, 833t
 tubular-finned, 794, 795
 tubular-plate, 794, 795
 Raschig rings, 575, 583
 Reattachment of layer, 401
 Recirculation, 181
 Rectangular plate, in a tube, three-dimensional
 flow, 697t
 Rectification column, 579
 Recuperators, 844t
 Reduced velocity, 32, 282
 Regeneration, 622
 Regime
 of quadratic resistance law, 140t
 bubbling, 785
 fluid flow, 18
 foam, 785
 laminar, 240
 laminar flow, 19
 replacement of, 90
 self-similar turbulent, 240
 square-law, 89
 transition, 240
 wavy, 785
 Relative spacing, 707
 Resistance
 drag, 669
 external frontal, 191
 nonuniform, 589
 shape, 665
 Resistance coefficients, 3, 50, 173
 converging and transition sections, 277
 diagrams of, 192–218t, 246–273t, 337–381t,
 424–477t, 592–612t, 627–660t, 680–701t,
 719–776t, 808–856t
 fluid, 42
 friction, 331

internal, 325, 329
 of bends, 391
 of compensators, 617
 of curved segments, 391
 of diffusers, 277
 of elbows, 391
 of exit sections, 705
 of grids, 575
 of inlet, effect of the wall on, 177
 of labyrinth seals, 617
 of manifolds, 483
 of packings, 575
 of plugs, 617
 of porous layers, 575
 of screens, 575
 of sections with apertures, 223
 of sections with diaphragms, 223
 of sections with girders, 663
 of sections with orifices, 223
 of sections with other shapes, 663
 of sections with protuberances, 663
 of sections with sudden contraction, 223
 of sections with sudden expansion, 223
 of sections with trusses, 663
 of tees, 483
 of throttling devices, 617
 of valves, 617
 of wyes, 483
 Resistance
 curve, 92, 101
 forces, 1
 Resistance to flow
 at entrance into conduits, 177
 at entrance into tubes, 177
 friction coefficients for, 85
 in conduits, 85
 in straight tubes, 85
 smooth change in velocity, 277
 through orifices, 223
 with changes of the stream direction, 391
 Reynolds number, 3, 18, 44, 55, 57, 86, 87, 283
 critical, 20
 low, 307
 Rolling paper, 402
 Rotation, 781

Roughness, 85, 294
 nonuniform, 91, 396
 ordered, 89
 protrusions, height of, 295
 relative, 86, 91, 782
 uniform-grain, 88

S

Screens, 184, 575, 598t, 599t
 at subsonic flow velocities (see Grids
 at subsonic flow velocities)
 corrugated, 786
 in series, 579
 noncontaminated, 577
 two-plane, 578
 Scrubbers
 air, 779
 centrifugal, 822t
 gas, 779
 Venturi, 784
 wet, 784
 wet, turbulent, 818t, 819t
 with wooden packing, 821t
 Seawater, density of, 10t
 Settling plates, 787
 Separation zone, 177, 309
 Separation, 86
 Separators, 850t
 Shafts
 fan, 80
 intake, 184, 209t
 mine, 675
 straight intake circular, 211t
 straight, 209t
 supercharger, 65
 ventilating, 184
 with bends, 210t
 Shaped part-fittings, combination, mutual
 effect of, 856t
 Sharp turns, 626
 Shock, 225
 Shock coefficient, 298, 301
 total, 326
 Short
 starting length, 101

- transition piece, 301
 - Side wall, 55
 - Similarity groups, 31
 - Simple transformations, 49
 - Sintering gases
 - installation, scrubbing of, calculation
 - of resistance, elements of the system, 73–76t
 - scrubbing of, 72
 - Slats, 779
 - Slits, 309
 - Sloping bottom, 186
 - Smoke discharging, 712
 - Smooth
 - entrance, 100
 - transition, 317
 - turning, 411
 - walls, 402
 - Smoothly expanding tubular section, 277
 - Smoothly rounded branch, 491
 - Spacers in a tube, plane-parallel flow, 684–687t
 - Spatial (annular) turn, 416
 - through 180 degrees, 418t
 - Specific energy, loss of, 46
 - Speed of sound, 32
 - Sphere, 666
 - in a tube, three-dimensional flow, 690t, 691t
 - Spillway, 623
 - Splitters, 316
 - Square-law regime, 89
 - Stabilizing effect, 419
 - Stagnation temperature, 32
 - Starlike shapes, 97
 - Static momentum, 36
 - Static pressure, 295
 - distribution of, 46
 - recovery, 231, 301, 310, 313
 - uniform distribution of, 43
 - Stationary hot gas, 23
 - Stopping device, 620
 - Straight
 - inlet section, 177
 - insert, 284
 - passage, 488
 - Stream
 - deformation, 18
 - discharged, 3
 - dusted, 52
 - Streamlines, 588
 - asymmetry of, 667
 - Subsonic flow, 34t
 - of fluid, 288
 - velocities, 292
 - Subsonic range, 289
 - Suction, 243
 - Sudden contraction, 180, 237, 254–256t
 - in transition and laminar regions, 255t, 256t
 - Sudden expansion, 237, 320, 485
 - velocity distributions of, 246–252t
 - Sulfur dioxide, density of, 10t
 - Superchargers, 40, 64
 - high-head, 66
 - Superposition
 - of losses, 42, 44
 - principle of, 45
 - Supersonic velocities, 102
 - Support plates, 102
 - Surface tension coefficient, 579
 - Swirler, 782, 800–801
 - blade, 783
 - conveyer-type, 802
 - Symmetric plane turn through 180 degrees, 419
 - Symmetrical
 - 180-degree turn, 417
 - velocity profile, 289
- T**
- Tangential injection, 315
 - Tape insert, 802
 - Tapered air ducts, 710
 - Temperature
 - correction for, 37
 - small differences, 52
 - Throttle, 806
 - Throttling devices, 298, 617, 618
 - Tortuous flow paths, 625
 - Total
 - energy (pressure) loss, 1
 - pressure loss factor, 313
 - resistance, 48

Trailing part, 674

Transition

- from rectangular to circular cross sections, 380t
- of a circle into a rectangle, 336
- of a rectangle into a circle, 336
- point, 401
- region, 93, 714
- sections, 332

Transition piece, 333, 618

- converging, 334
- converging-diverging, 332, 377t, 378t
- diverging, 334
- length of, 335
- with sharply changing cross sections, 379t

Transverse

- bundle of finned tubes, 840t
- distribution, 23
- self-oscillations, 679
- tube bundle, with different
 - cross-sectional shapes, 841t, 842t

Trays

- bubbling, 579, 580
- wetting, 579

Triangles

- equilateral, 100
- equilateral rectangular, 100
- isosceles, 99

Truss, 675

- in a tube, plane-parallel flow, 700t, 701t

Tubes

- and channels, 426–428t
- annular concentric, 127
- annular, 664
- bundles, 147–149t, 795
- circular annular, 98
- circular with rough walls, 140t
- circular with smooth walls, 133t
- circular with walls of nonuniform roughness,
 - 138t, 139t
- circular with walls of uniform roughness,
 - 134–137t
- commercial, 92
- curved, 392
- eccentric annular, 99
- elliptical, 98

- entrance into various types, 192–196t, 203–208t
- entry through first side orifice, 207t, 208t
- entry through orifices, 203–205t
- equilateral triangle, 96
- equivalent roughness of surfaces,
 - types/materials of tubes, 120–126t
- finned, 799
- flat-rolled, 103
- flat-rolled aluminum, 103
- flat-rolled steel, 103
- flexible corrugated, 108
- flow deformation in, 252–254t
- helical, 398
- noncircular, 97
- nonrotating, 803
- nonstabilized flow, 161t, 162t
- parallel interstitial flow in, 147–149t
- porous, 111
- rectangular, 98
- reinforced by various spacers and braces,
 - across the section, along the channel, 700t
- rotating, 803
- seamless, 104
- settling, 788
- smooth inlet, 161t, 162t
- smoothly curved, 396
- spirally corrugated, 802
- square, 227
- stabilized flow in various types, 133–147t,
 - 150–153t, 157–160t
- straight, pressure losses in, 85
- tension, 157t
- with screen at the inlet, 206t

Turbines, 329

Turbo machines, 187

- axial stationary, 213t

Turbulence

- degree of, 44
- scales, 590

Turbulent

- agitation, 41
- mixing, 484

Turbulization, 400

Turbulizer, 591

Turns

- and bends, 428t, 429t
- and elbows, in system of pneumatic transport, 475–477t
- and elbows, joined, curved, 455–457t
- and elbows, of rectangular cross section, 463t, 464t
- conventional, 495
- spatial (circular), through 180 degrees, (during suction), 469t, 470t
- spatial (circular), through 180 degrees, (with pumping), 471t, 472t
- symmetric, through 180 degrees, in one plane, (during suction), 473t, 474t
- with concentric guide vanes, 465t

U

Uniform velocity distribution, 3

V

Valve

- ball, on a spherical seat, 654t
- butterfly, 618
- butterfly, in a tube of circular cross section, 646t
- butterfly, throttling, in a tube of rectangular cross section, 647t
- check, with screen, 651t
- conical, 621
- conical, on a conical seat, 653t
- conical, on a flat seat, 654t
- cylindrical, in the system, 645t
- disk, 618
- disk, under complex conditions, 654t, 655t
- disk, with bottom guides, 652t, 653t
- disk, without bottom guides, 651t, 652t
- gate, 617, 618
- globe, 617
- regulating, 619, 650t
- single-seat, 619
- suction, with screen, 651t
- throttling, in a tube of circular cross section, with disk gates of different shape, 649t
- throttling, thin-walled disk, with parallel and nonparallel flaps, 648t

- various types of gate, 627t
- various types of globe, 627t

Vanes

- arc, optimum angle of, 414
- concentric, 415
- guide, 410, 711
- screw, 783
- swirl, 783
- thin shaped, 414

Velocity

- coefficient, 56
- distribution, 44, 403
- fields, 280
- profiles, 44, 130
- retardation, 329

Ventilating hoods, 805

Ventilators

- dome, 805
- rectangular roof, with panels, 850t
- roof, 848t, 849t

Vessel bottom, 55

Viscosity

- dynamic, 12
- kinematic, 12
- units of, 13t

Viscous

- forces, 48, 86
- resistance force, 48
- sublayer, 87

Volumetric

- flow, 45
- gas content, 422
- generators, 320
- pair, 393
- single toroidal, 668

Vortices

- formation of, 41
- random, 668
- shedding of, 668
- stalling of, 285

W

Wake, 666

- attached, 668
- toroidal vertical, 667

- Wall mount, 198t, 199t
 - with facing baffle, 198t
- Water, density of, 10t
- Welding seams, 406
- Wet scrubber, 72, 73t
- Wind energy, 805
- Wind tunnels, 591
 - calculation of resistance, types of elements, 78–80t
 - closed-circuit, 77
 - low-velocity, 77
 - open-throat, 77
 - working section (open) of, 273t
- Wire net, 324
- Wood oil, density of, 10t
- Wooden laths, 583
- Working section, 80
- Wyes
 - converging, 484, 491, 501–509t
 - convergent, nonsymmetric, 542–543t
 - converging, of improved shape, 511–515t
 - converging, of industrial construction, 522t
 - converging, of normalized construction, 517–521t
 - converging, smooth, 516t
 - converging, threaded, 510t
 - diverging, 485, 523–527t, 529–534t
 - diverging, of normalized construction, 538–540t
 - diverging, smooth, 541t, 542t
 - double, 496
 - equilateral, 494
 - four-way, 556–562t
 - nonstandard, 483
 - nonstandard diverging, 489
 - of improved shape, 535–538t
 - of rectangular cross section, 483
 - symmetrical, 495
 - symmetrical (equilateral), 543–555t
 - threaded, 528t
 - welded, 492
 - with branches, 490
 - with screwed pipes, 492
- Wye-collector, sectional, effect of, 855t