

## INDEX

### A

- Absorption
  - of radiation in gases, 145–150
- Absorption cycles, 835–838
  - Electrolux refrigeration cycle, 837–838
  - simple absorption cycle refrigerator, 835–837
- Absorptivity of radiation
  - monochromatic directional, 132
  - monochromatic hemispherical, 132
  - total, 132
- Acetic acid, saturation properties of, 1006
- Acetone, saturation properties of, 1007
- Acetylene, saturation properties of, 993
- Active methods, for enhancement of heat transfer, 886–890
- Adiabatic saturation temperature, 752–756
- A-frame air-cooled condensers, 677
- Agitated vessels, heat transfer in, 937–953
  - agitation within vessel, 937–940
    - nonproximity systems, 939
    - proximity systems, 939
  - heat transfer and pressure drop in coils, 941–945
  - heat transfer on inside of vessel wall and on immersed vertical coils, 945–953
  - jacket (and limpet coil) heat transfer, 940–941
- Ahmad scaling method, for critical heat flux in tubes, 460–463
- Air
  - gaseous, atmospheric pressure, properties of, 1018
  - saturation, properties of, 1008
- Air conditioning, 4, 829–835
- Air-cooled condensers., 650–652, 675–685
  - A-frame, 677
  - application of, 675–676
  - design of, 680–683
  - flow arrangement for, 676–680
    - combined down flow and reflux, 679
    - down flow (inclined tube), 678–679
    - horizontal tube, 679
    - reflux (inclined tube), 679
    - vertical tube, 679–680
  - maldistribution effect in, 684
  - mounting arrangements for, 676
    - column mounted, 676
    - ground mounted, 676
  - noise generation in, 684–685
- Air-cooled heat exchangers, 365–389
  - advantages and disadvantages, 365
  - construction, 365–371
    - bundle construction, 367–368
    - finned tube construction, 368–371
    - forced draft, 366
    - induced draft, 366
  - description, 213, 365–371
  - in air conditioning systems, 823–832
  - thermal performance calculation, 371–389
    - effects of tube configuration on, 387
    - for condensation duty, see air-cooled condensers
    - mean temperature difference, 372
    - overall heat transfer coefficient, 371
    - rating calculations for, 373–387
    - typical U and C values for, 229
- Air-water system, 751–762
  - adiabatic saturation temperature, 752–756
  - enthalpy relationships, 756
  - humidity, 751–752
  - psychometric chart, 756–762
    - application to dryers, 757–759
    - application to humidification, 759–762
    - application to mixing of streams, 759–760
  - psychometric ratio, 755
  - wet bulb temperature, 752–756
- Ammonia
  - gaseous, atmospheric pressure, properties of, 1018
  - saturation properties of, 1009
- Analogies between heat and mass transfer, 62–64
  - Chilton-Colburn analogy, 63–64
  - in heat transfer enhancement, 882–883
  - Reynolds analogy, 62–63
  - use in direct contact heat transfer, 714–715
- Anchor agitators, for agitated vessels, 939
- Aniline, saturation properties of, 1006
- Annular flow,
  - in horizontal tubes, 392
  - in vertical tubes, 391
- Antifoulants, 876
- Argon, saturation properties of, 1009
- Assisted draft cooling tower, 749
- Asymptotic resistance, due to fouling, 858
- Augmentation of heat transfer, see Enhancement of heat transfer
- Azeotrope formation, 435

### B

- Basketweave checkerwork, for regenerative heat exchangers, 898
- Bayonet tube evaporator, 560
- Bayonet tube waste heat boiler, 493
- Beer's Law, of absorption of radiation in gases, 144–145
- Bell's approximate method for condensers with desuperheating, 666–668
- Bell-Delaware method, for heat transfer and pressure drop in shell-and-tube exchangers, 275–285
- Bends, pressure drop in two-phase flow in
  - homogenous model for, 401–402
  - separated flow model for, 410
- Benzene, saturation properties of, 990
- Binary mixtures, mass transfer in, 606–613

- Biological fouling, 863
  - Biological reactions, heat transfer in, 2
  - Biot number, 47
  - Blackbody radiation, 120–126
    - Planck's distribution for, 121
    - radiation intensity in, 123–126
      - emissive power, 125
      - Lambert's cosine law for, 124
    - Stefan-Boltzmann law for, 122
    - view factor between blackbodies, 136
  - Blasius equation, for pipe flow friction factor, 97
  - Boiling crisis, see critical heat flux
  - Boiling heat transfer, 423–467
    - critical heat flux in, 454–465
      - in forced convective boiling, 455, 458–463
      - in pool boiling, 455–458
    - correlation for boiling heat transfer coefficients, 442–454
      - in combined nucleate and forced convective boiling, 449–453
      - in forced convective boiling, 448–449
      - in nucleate boiling, 442–448
      - in postdryout region, 453
    - cross-flow boiling, 430–433
      - in kettle reboilers, 527–528
    - enhancement of heat transfer in, 891–893
    - forced convective boiling, 429–430
      - critical heat flux in, 455, 458–463
      - heat transfer coefficients in, 448–449
      - of multicomponent mixtures, 438–442
    - pool boiling, 428–429
      - critical heat flux in, 455–458
      - of multicomponent mixtures, 436–438
      - regimes in, 428
    - multicomponent boiling, 433–442
    - vapour formation, 423–428
      - critical bubble radius for, 425
      - heterogeneous nucleation, 425–428
      - homogenous nucleation, 425
  - Boiling length, 458
  - Boiling point, normal, of selected substances, 983–1017
  - Boltzmann constant, 121
  - Boundary layer
    - in the entrance region of a tube, 102
    - in the entrance region of pipes, 57
    - on flat plate, 57–58
      - convective heat transfer in, 64–69
      - thermal boundary layer, 58
      - velocity boundary layer, 57
  - Bouré and Mihaila method, for onset of density wave instability, 530
  - Bowring correlation, for critical heat flux for water flowing in tubes, 459–460
  - Boyko and Kruzhilin correlation, for shear controlled condensation, 588–589
  - Brayton cycle, for gas turbines, 811–813
  - Brickwork, for regenerative heat exchangers, 898
  - British Standard Quadrature method for solving
    - Merkel integral in cooling tower design, 765–766
  - Bubble
    - critical radius for growth of, 425
    - heterogeneous nucleation of, 425–428
    - homogenous nucleation of, 425
  - Bubble columns, for direct contact heat transfer, 699–702
    - fluid dynamics of, 715–717
  - Bubble flow
    - dispersed in horizontal tubes, 391–392
    - in vertical tubes, 391
    - in cross-flow over tube banks, 397
  - Bubble point, 615
  - Bubble type direct contact condenser, 726–729
    - theoretical models for, 740–744
  - Burnout, (see critical heat flux)
  - 1,2-Butadiene, saturation properties of, 996
  - 1,3-Butadiene, saturation properties of, 996
  - n*-Butane, saturation properties of, 985
  - n*-Butanol, saturation properties of, 999
  - t*-Butyl Alcohol, saturation properties of, 999
- ## C
- C-value method, for approximate costing of heat exchangers, 215–231
    - air-cooled heat exchangers, 229
    - double pipe exchangers, 223–225
    - gasketed plate exchangers, 226–228
    - shell-and-tube exchangers, 220–222
    - typical C-values, 220–229
  - Carbon dioxide
    - gaseous, atmospheric pressure, properties of, 1019
    - saturation properties of, 1010
  - Carbon monoxide
    - gaseous, atmospheric pressure, properties of, 1019
    - saturation properties of, 1010
  - Carbon tetrachloride, saturation properties of, 1011
  - Carnot cycle, 809
  - Cavities
    - natural convection in, 117–119
    - radiation in, 140
  - Checkerwork, for regenerative heat exchangers, 898
  - Chemical formulae, of selected substances, 983–1017
  - Chemical reaction fouling, 863
  - Chemical reactions, heat transfer in, 2
  - Chen correlation, for forced convective boiling, 450
  - Chen equation, for pipe friction factor, 98
  - Chilton-Colburn analogy, 63–64
  - Chisholm correlations
    - for shell-and-tube heat exchangers, 412–413
    - for two-phase pressure drop in changes of cross section and bends, 409–410
    - for two-phase pressure drop in pipes, 402–405
  - Chlorine, saturation properties of, 1011
  - Chloroform, saturation properties of, 1005
  - Churn flow, 391
  - Circulation rate, in fossil fuel fired boilers, 488
  - Clapeyron-Clausius equation, for vapour liquid equilibrium, 424
  - Cleaning, of foulant from heat exchangers, 875–876

- Climbing film evaporator, 550–552
- Coefficient of performance, in thermodynamic cycles, 808–811
- Coils, for agitated vessels
  - heat transfer inside, 941–945
  - heat transfer on outside of, 945–953
- Colburn equation, for turbulent heat transfer in a pipe, 105
- Colburn-Drew method, for binary vapour condensation, 624–627
- Colburn-Hougen method, for condensation in presence of inert gas, 621–624
- Colburn j-factor, 298, 616
- Combined gravity and shear controlled condensation, 589–590
- Compact heat exchangers, 213–214, 297–325
  - plate-fin type, 297–325
    - design procedure, 323–324
    - heat transfer and pressure drop in, 298–312
    - performance calculation, 312–323
    - structural features of, 297–300
- Composite curves, in process integration, 841–849
  - minimum energy requirement, 843
  - the “pinch”, 844, 848
- Condensation, 573–641
  - enhancement of heat transfer in, 890–891
    - equivalent laminar film model for, 599–604
  - filmwise (combined gravity and shear controlled), 589–590
    - in horizontal tubes, 589–590
  - filmwise (gravity controlled)
    - inside horizontal tubes, 593–595
    - on vertical flat plates, 574–580
    - outside horizontal tubes, 590–593
  - filmwise (shear controlled), 580–590
    - in horizontal tubes, 593
  - in multicomponent systems, 599–639
    - Colburn-Drew method for, 624–627
    - Colburn-Hougen method for, 621–624
    - condensation curves for, 628–635
    - Silver-Bell-Ghaly method for, 635–639
  - modes of, 573–574
    - dropwise, 574
    - filmwise, 573
    - homogeneous, 573–574
    - immiscible liquid, 574
- Condensation curve, 436, 628–635
- Condensers
  - air-cooled condensers, 650–652, 675–685
    - applications of, 675–676
    - design of, 680–683
    - flow arrangement, 676–680
    - maldistribution effects in, 684
    - mounting arrangement for, 676
    - noise generation in, 684–685
  - direct contact condensers, 654–657
    - baffle column type, 655–656
    - spray type, 654–656
  - plate-and-frame (gasketed plate) heat exchangers
    - as condensers, 652–653, 687–690
    - heat transfer calculations for, 690
      - pass arrangements for, 687–688
      - pressure drop in, 689
  - plate-fin heat exchangers as condensers, 653–654, 690–691
  - reflux, 646
    - flooding in, 417–419
  - selection of, 644–646
  - shell-and-tube condensers, 646–650
    - condensation of multicomponent mixture in, 668–673
    - desuperheating and subcooling in, 663–668
    - horizontal shell-side, E-shell, 647
    - horizontal shell-side, J-shell, 647
    - horizontal shell-side, rod baffled, 649
    - horizontal shell-side, X-shell, 647
    - horizontal tube-side, 646
    - mean temperature differences in, 662–663
    - pressure drop in, 673
    - shell-side heat transfer in, 660–662
    - vertical shell-side, 646
    - vertical tube-side, 646
- Conduction, of heat, 12–55
  - Fourier's law of, 12
  - general equation for, 16–19
    - in Cartesian coordinates, 16–18
    - in cylindrical geometry, 18
    - in spherical geometry, 19
  - in fins, 27–31
    - fin effectiveness, 30
    - fin efficiency, 31
    - infinitely long fin, 29
  - steady-state, 19–27
    - one-dimensional, 19–20
    - radial, in cylinders, 21–23
    - spherical, in spheres, 23–24
    - thermal resistance, general expression for, 26–27
  - thermal conductivity, 13–16
  - transient, 42–55
    - in semiinfinite solids, 44–47
    - with convection and radiation, 47–55
  - two-dimensional, 32–36
    - graphical method for, 32
    - shape factor, 34–36
  - with internal heat generation, 36–42
    - cylinder, 38–41
    - flat plate, 36–38
- Continuity equation (two-phase flow)
  - homogeneous model, 399
  - separated flow model, 400–401
- Contraction, sudden, pressure drop in two-phase flow
  - homogeneous model for, 401
  - separated flow model for, 410
- Convective heat transfer, 55–119
  - at a flat plate, 64–69
    - Chilton-Colburn analogy for, 63–64
    - enhancement of, 879–890
    - in boundary layers, 57–58, 64–69
    - in cross-flow over a cylinder, 69–73
    - in internal flows, 94–108
    - in natural convection, 108–119

in tube arrays, 73–93  
   finned tube arrays, 82–93  
   plain tube arrays, 73–82  
 laminar and turbulent flow, 56–57  
   Reynolds number, 56  
 nondimensional parameters for, 58–64  
 regimes of, in horizontal pipes, 99  
 Reynolds analogy for, 62–63  
 Cooling towers, 747–776  
   as gas-liquid contactors, 704  
   assisted draft counterflow type, 749  
   assisted draft cross-flow type, 749  
   forced draft counterflow type, 747  
   induced draft counterflow type, 747  
   induced draft cross-flow type, 747  
   natural draft counterflow type, 747  
   natural draft mixed flow type, 749  
   Merkel method for prediction of, 762–771  
     British Standard quadrature method for, 765  
     Merkel integral, 765  
     packing function, 765, 768  
   packings for, 767  
     packing function, 765  
     pressure loss in, 772  
   pressure drop in, 772–775  
 Cooper correlation, for nucleate boiling, 444–445  
 COP, see Coefficient of performance  
 Corrosion fouling, 864  
 Corrugation forms, in plate-and-frame heat exchangers, 330  
 Costs, of heat exchangers, see C-value method  
 Countercurrent flow heat exchanger, see pure countercurrent flow heat exchanger  
 Cowper stove, 895  
 Critical bubble radius, for growth, 425  
 Critical density, of selected substances, 983–1017  
 Critical heat flux, 454–465  
   as limitation in design of vapour generators, 483  
     in cross-flow, 528–530  
   in forced convective boiling  
     correlations for, 458–465  
     mechanisms for, 455  
   in pool boiling,  
     correlations for, 455–458  
     mechanisms of, 454–455  
 Critical mass flow rate, in two-phase flow, 416–417  
 Critical pressure, of selected substances, 983–1017  
 Critical temperature, of selected substances, 983–1017  
 Cross-flow  
   drag coefficient for flow over cylinders in, 70  
   heat transfer for flow over cylinders in, 70–72  
   over finned tube arrays, 82–93  
     heat transfer in, 84–89  
     pressure drop in, 89–93  
   over plain tube arrays, 73–82  
     heat transfer in, 73–76  
     pressure drop in, 79–80  
   two-phase flow patterns in, 394–397  
   two-phase pressure drop in, 412–413  
   two-phase void fraction in, 527  
 Cross-flow boiling, 430–433  
   in kettle reboilers, 524–527

Cross-flow heat exchangers, 180–181  
 Crystallisation fouling, 862  
 Cyclic regenerators, 210, 895  
   calculation of, 905–906  
 Cyclohexane, saturation properties of, 990  
 Cyclopentane, saturation properties of, 989  
 Cylinders  
   coaxial, radiation between, 142–143  
   critical heat flux for pool boiling from, 455–458  
   fluid flow over, 69–70  
     drag coefficient for, 70  
   general equations for conduction in, 18  
   heat transfer from in cross-flow, 70–72  
   natural convection from, 116–117  
   overall heat transfer coefficient for, 155–161  
   steady-state conduction in, 21–23  
   with internal heat generations, 39–41

## D

*n*-Decane, saturation properties of, 989  
 Density  
   of gases, at atmospheric pressure, 1018–1021  
   of metals, 1022–1025  
   of selected substances under saturation conditions, 983–1017  
 Density wave instability, in boiling, 485  
   Bouré and Mihaila method for estimating onset of, 530–531  
 Design  
   of air-cooled condensers, 680–683  
   of multicomponent condensers, 627–628  
     approximate (Silver-Bell-Ghaly) method, 635–636  
   of plate-and-frame heat exchangers, 357  
   of plate-fin heat exchangers, 323–324  
   of shell-and-tube heat exchangers, 292–295  
   of vapour generators, 479–481  
     limiting factors in, 481–485  
 Desuperheating, in condensers, 663–668  
   dry-wall desuperheating, 664  
   wet-wall desuperheating, 664–668  
     Bell's approximate method for, 666–668  
     detailed calculations, 664–668  
 Dew Point, 613–615  
 Dielectric heating, 928–932  
   energy penetration and uniform heating, 929  
   equipment selection for, 932  
   practical aspects, 929–931  
     frequencies, 929  
     loss factors of common materials, 930  
     voltage, 929  
   simple theory, 928–929  
   types of microwave applicators, 931  
     serpentine, 931  
     multimode, 931  
   types of radiofrequency applicators, 931–932  
     heating platen, 931  
     staggered through field, 932  
     stray field electrode, 932

- Diffuse emitter, 130
  - Dimethyl propane, saturation properties of, 984
  - Direct contact condensers
    - baffle column type, 655–656
    - spray type, 654–656
  - Direct contact condensers, 725–745
    - bubble type, 726–729
      - theoretical models for, 740–744
    - drop-type, 725
      - drop heat transfer, 731–733
      - drop velocity and displacement, 730–731
    - film type, 726
      - condensation in packed bed, 739–740
      - correlation for, 738–739
    - jet and sheet type, 726
      - theoretical models for, 734–738
  - Direct contact evaporators, 473–474, 563–565
  - Direct contact heat exchangers, 5, 698–722
    - for evaporation, 473–474, 563–565
    - gas-liquid contactors, 698–704
      - bubble columns, 699–703
      - packed columns, 699
      - perforated plate columns, 699–703
      - spray and jet contactors, 703
      - spray columns, 699
      - water cooling towers, 704, 747–776
    - liquid-liquid contactors, 704
    - solid-fluid contactors, 704–706
  - Direct contact heat transfer, 693–722
    - basic generic theory for, 706–722
    - for condensation duty, 725–745
      - baffle column type, 655–656
      - bubble-type, 726–729, 740–744
      - drop-type 725, 730–733
      - film-type, 726, 738–740
      - jet- and sheet-type, 726, 734–738
    - fluid dynamic models for, 715–722
      - flooding in packed columns, 719–722
      - flooding in tubes, 718–719
      - in spray columns, 717–718
      - in bubble columns, 715–717
    - gas-liquid heat transfer, 695–696
      - with gas phase continuous, 695
      - with liquid phase continuous, 695–696
    - liquid-liquid heat transfer, 696
    - solid-fluid heat transfer, 696
      - heat and mass transfer analogy, 714–715
      - NTU approach, 712–714
  - Dispersed bubbly flow, 392
  - Displaced enhancement devices, for enhancement of heat transfer, 881
  - Dittus-Boelter equation, for turbulent heat transfer in a pipe, 105
  - Double pipe heat exchangers, 233–261
    - advantages of, 235–236
    - description of, 200–201, 233–235
    - mechanical features of, 233–235
    - multitube units, 260
    - parallel/series arrangement for, 247–253
    - thermal performance of, 236–260
      - mean temperature difference, 240–241
    - typical U and C values for, 223–225
  - Double tube quench waste heat boiler, 493
  - Dowtherm A, saturation properties of, 1007
  - Dowtherm J, saturation properties of, 1008
  - Drag coefficient
    - for flow over cylinder, 70
  - Droplets, use in enhancement of heat transfer, 886
  - Drop-type direct contact heat exchanger, 725
    - drop heat transfer in, 731–733
    - drop velocity and displacement in, 730–731
  - Dropwise condensation, 574
  - Dryers, application of psychrometric chart to, 757–759
  - Dryout, see Critical heat flux
    - in fossil fuelled boilers, 488
  - Dry-wall desuperheating in condensers, 664
  - Dynamic instabilities, in boiling, 484–485
    - density wave, 484–485
    - due to compressible volumes, 484
    - parallel channel, 484
- ## E
- Effectiveness, of heat exchangers, 182–183
    - charts for estimation of, see Mean temperature difference relationships
    - in plate-and-frame exchangers, 338
    - in regenerative heat exchangers, 905
    - table of equations for, 958
  - Efficiency, in thermodynamic cycles, 808–811
  - Efficiency, of fins, 31, 84–85, 88–89
  - Electrical heating, 915–936
    - dielectric heating, 928–932
      - energy penetration and uniform heating, 929
      - practical aspects, 929–931
      - simple theory, 928–929
      - types of microwave applicators, 931
      - types of radiofrequency applicators, 931–932
    - induction heating, 923–928
      - basic concepts, 924–926
      - practical aspects, 926–927
    - infrared heating, 932–936
      - selection of equipment for, 936
    - resistance heating, 915–923
      - basic theory, 916–917
      - direct, 923
      - indirect, 917–923
  - Electrical resistivity, of metals, 919
  - Electrolux refrigeration cycle, 837
  - Emissive power
    - monochromatic, 121
    - total, 122
  - Emissivity
    - monochromatic directional, 126
    - of gases, 145–147
    - table of, for various surfaces, 128–130
    - total hemispherical monochromatic, 126
    - total (hemispherical), 127
    - total (monochromatic), 126
  - Emitter, diffuse, 130
  - Energy utilisation, in the process industries, 1–3
  - Engine driven heat pumps, 832–835
  - Engineering Sciences Data Unit, see ESDU

Enhancement of heat transfer, 879–894  
 acceptance criteria for, 893  
 active methods for, 886–890  
   scraped surface exchangers, 886–889  
   surface vibration, 889  
 compound techniques, 890  
 in boiling and evaporation, 881–893  
 in condensation, 890–891  
 passive methods for, 879–886  
   alternative methods for, 881  
   in forced convection heat transfer, 881–885  
   in free convection heat transfer, 881  
 Enlargement, sudden, pressure drop in two-phase flow in  
   homogeneous model for, 401  
   separated flow model for, 410  
 Enthalpy  
   in the air-water system, 756  
 Entrance length, in laminar flow heat transfer, 101  
 Equivalent diameter, 106–107  
   in plate-fin heat exchangers, 306  
 Equivalent laminar boundary layer model for convective heat and mass transfer, 59–60  
 ESDU (Engineering Sciences Data Unit) correlations  
   for heat exchanger effectiveness  
     example, 185  
     index to sources, 979–980  
   for heat transfer from plain tube arrays, 73–79  
   for heat transfer in low-finned tube arrays, 85–87  
   for heat transfer in high-finned tube arrays, 87–88  
   for turbulent heat transfer in tubes, 104  
 Ethane, saturation of properties of, 983  
 Ethanol, saturation properties of, 997  
 Ethyl acetate, saturation properties of, 1005  
 Ethyl benzene, saturation properties of, 993  
 Ethylene oxide, saturation properties of, 1003  
 Ethylene, saturation properties of, 994  
 Ethyl ether, saturation properties of, 1002  
 Evaporators, 537–571  
   direct contact, 563–565  
   film type, 537–552  
     climbing film, 550–552  
     falling film, 539–541  
     heat transfer in, 541–550  
   flash evaporation, 560–563  
   for heat pump systems, 820–835  
     in refrigerators, 823  
     in liquefaction of gases, 829  
   multiple effect evaporators, 565–570  
   selection of type, 565  
   with nucleate boiling, 552–560  
     basket type, 552–553  
     bayonet type, 560  
     helical coil type, 560  
     horizontal shell-side, 559–560  
     long tube vertical, 553–557  
     plate-fin type, 557–558  
     short tube vertical, 552  
     spiral plate type, 558  
 Extended surfaces (see also Fins, Finned tube arrays)  
   in air-cooled heat exchangers, 367–371  
   in plate-fin heat exchangers, 298

## F

F-correction factor  
   charts for, see Mean temperature difference relationship  
   definition of, 175  
 Falling films  
   heat transfer in evaporation, 541–550  
     smooth laminar film, 542–547  
     turbulent film, 550  
     wavy laminar film, 547–550  
   in evaporators, 539–541  
 Films, falling (see Falling films)  
 Film-type direct contact condenser, 726  
   condensation in packed bed, 739–740  
   correlations for, 738–739  
 Film-type evaporators, 537–552  
   climbing film, 550–552  
   falling film, 539–541  
   heat transfer in, 541–550  
     smooth laminar film, 542–547  
     turbulent film, 550  
     wavy laminar film, 547–550  
 Filmwise condensation  
   combined gravity and shear controlled, 589–590  
     in horizontal tubes, 590–595  
   description, 573  
   gravity controlled  
     inside horizontal tubes, 593–595  
     on vertical flat plate, 574–580  
     outside horizontal tubes, 590–593  
   shear controlled, 589–590  
     in horizontal tubes, 593  
 Finned tube arrays  
   geometric factors, 82–84  
   high-fin tubes, 87–88  
   in air-cooled heat exchangers, 367–368  
   low-fin tubes, 85–87  
 Fins  
   conduction in, 27–31  
   effectiveness of, 30  
   efficiency of, 31, 84–85, 88–89  
     in plate-fin exchangers, 315, 321–322  
   longitudinal, in double pipe exchanger, 253–259  
 Fire tube boilers  
   fossil fuel fired, 487–490  
   horizontal (cross-flow) waste heat, 497–498  
 Fixed bed regenerators, 211, 895  
   calculation of, 905–906  
 Flash evaporation, 560–590  
 Flashing, for vapour generation, 473, 561–563  
 “Flat pancake” waste heat boiler, 493  
 Flat plate  
   boundary layer on, 57–58  
   conduction in, 36–38  
   convective heat transfer from, 64–69  
     laminar flow, 64–65  
     turbulent flow, 65–66  
   critical heat flux for pool boiling from, 455–458  
   filmwise condensation on, 574–590

- natural convection from, 111–116
  - overall heat transfer coefficient for, 155–158
  - radiation between, 148–149
  - Flooding (in countercurrent two-phase gas-liquid flow), 417–420
    - as limitation of design of vapour generators, 482–483
    - in packed columns, 719–722
    - in reflux condensers, 418–420
    - Wallis correlation for, 418, 718–719
  - Flow enthalpy, 843
  - Flow patterns (in gas-liquid flow), 391–420
    - in cross-flow and shell-and-tube heat exchangers, 394–396
    - in horizontal tubes, 391–394
      - Taitel and Dukler map for, 394–395
    - in inclined tubes, 394
    - in vertical tubes, 391
      - Hewitt and Roberts map for, 393
  - Flow stream analysis method for shell-and-tube heat exchangers, 285–292
  - Flue gas heated waste heat boilers, 491–492
    - horizontal tube type, 491–492
    - water-tube type, 491
  - Fluorine, saturation properties of, 1012
  - Forced convective boiling
    - critical heat flux in, 454–465
      - correlations for, 455–458
      - heat transfer coefficients in, 448–449
      - in multicomponent systems, 438–442
      - postdryout heat transfer in, 453–454
      - regimes in, 430–431
  - Forced draft air cooled heat exchangers, 366
  - Forced draft cooling towers, 747
  - Forster and Zuber correlation, for nucleate boiling, 443–444
  - Fossil fuel fired boilers, 487–490
    - circulation rate in, 488
    - dryout in, 488
    - fire-tube type, 487
    - instability in, 488
    - steam separation in, 488
    - water quality control in, 488
    - water-tube type, 487
  - Fouling, of heat exchangers, 857–877
    - antifoulants, 876
    - biological fouling, 863
    - chemical reaction fouling, 863
    - cleaning, 875
    - corrosion fouling, 864
    - crystallisation fouling, 862
    - economic penalties of, 875–876
    - effect of conditions on, 864–866
      - foulant concentration, 866
      - shear stress, 866
      - temperature, 864–865
      - velocity, 865
    - effect on heat transfer, 860
    - effect on pressure drop, 860–862
    - fouling resistance, 857–860, 867
      - asymptotic or “plateau” value, 858
      - effect of turbulent bursts on, 859
      - freezing fouling, 864
      - influence on operation of heat exchangers, 866–867
      - mixed fouling, 864
      - particulate fouling, 862–863
      - tables of, 872–874
      - variation with time, Kern-Seaton equation for, 858
  - Fourier's law, of conduction, 12
  - Fourier number, 740
  - Freezing fouling, 864
  - Friction factor
    - definition of, 58
    - in homogeneous two-phase flow, 401
    - in pipe flow, 96–98
    - on flat plate, 64–69
  - Friedel correlation, for two-phase pressure drop in pipes, 405–406
  - Fuels, characteristics of, 782–783
    - gaseous, 782
    - solid and liquid, 783
  - Furnaces, 777–805
    - heat transfer in, 778–788
      - effect of tube geometry, 786–788
      - heat balance in, 779–781
      - heat sink, 784–785
      - hot gas as heat source, 781–784
    - types used in process plants, 777
- ## G
- Gases, radiation in
    - Beer's Law of absorption in, 144–145
    - emissivity calculation for, 145–147
    - heat transfer from gas to surface, 147–148
    - intervention in radiation between parallel plates, 148–149
  - Gasketed plate heat exchanger, see Plate-and-frame heat exchanger
  - Gas-liquid contactors, for direct contact heat transfer
    - bubble columns, 699–703
    - heat transfer in, 698–703
    - packed columns, 699
    - perforated plate columns, 699–703
    - spray columns, 699
    - spray and jet contactors, 703
    - water cooling towers, 704, 747–776
  - Gas-liquid direct contact heat transfer, 695–696
    - with gas phase continuous, 695
    - with liquid phase continuous, 695–696
  - Gas-liquid flow, see Two-phase flow
  - Gas-to-gas heat exchangers, 207–210
  - Gas-to-liquid exchangers, 205–207
  - Gas turbines, 811–818
    - Brayton cycle for, 811–814
    - heat exchangers for heat recovery from, 813–814
    - regenerators, 813
    - waste heat recovery, 813–814
  - Graetz number, 102
  - Grant flow pattern map, for cross-flow over tube banks, 398
  - Graphical method, for two-dimensional conduction, 32–36
  - Grashof number, 98, 110–111

- Gravity controlled filmwise condensation
  - inside horizontal tubes, 593–598
  - on vertical flat plate, 574–580
  - outside horizontal tubes, 590–593
- Gregorig surfaces, for enhancement of condensation heat transfer, 891
- Groeneveld correlation, for postdryout heat transfer, 453

## H

- Heat conduction, see Conduction
- Heat engines, 807, 811–820
  - Carnot cycle for, 809
  - efficiency and coefficients of performance of, 808–811
  - gas turbines, 811–818
  - in process integration, 851–853
  - steam turbines, 818–820
- Heat exchangers
  - air-cooled, 213, 365–389
  - basic theory of, 155–195
    - effectiveness, 182–183
    - E/R/NTU method, 183–184
    - for cross-flow exchangers, 180–181
    - for shell-and-tube exchangers, 170–179
    - general calculation method of, 162–167
    - NTU, 183–184
    - P/R/NTU method, 184
    - $\theta$ /NTU method, 184–193
    - overall heat transfer coefficient, 155–161
    - specific solutions for constant heat transfer coefficient and heat capacity, 167–181
    - temperature profiles in, 162–164
  - classification of, 4–7
  - compact, 213–214, 297–325
    - plate-fin type, 297–325
  - cyclic regenerators, 212, 895–896
  - design of networks of, by process integration, 849–851
  - direct contact, 5, 693–745
  - double pipe, 200–201, 233–261
    - mechanical features, 233–235
    - multitubular units, 260
    - thermal performance, 236–260
  - for waste heat recovery from gas turbines, 813–814
  - gas-to-liquid, 205–207
  - gas-to-gas, 207–210
  - heat exchanger/process configuration, 4
  - heat pipe, 210–211
  - lamella, 204
  - plate-and-frame, 201–203, 327–363
    - heat transfer and pressure drop in, 331–335
    - thermal performance calculation of, 336–362
  - regenerative, 895–913
  - rotary regenerators, 212–213, 896–897
  - scraped surface, 215, 886–889
  - selection of, 197–233
    - initial selection, 215
    - selection between feasible types (C-value method), 215–231
  - shell-and-tube, 198–200, 263–296
    - heat transfer and pressure drop in, 269–295
    - mean temperature difference in, 170–179
    - mechanical features of, 265–269
  - spiral, 203–204
  - transmural, 5
  - welded plate, 205
  - with vapour condensation, see Condensers
  - with vapour generation, see Vapour generators
- Heat loss, from pipe, effect of lagging on, 24–26
- Heat pipe heat exchanger, 210–211
- Heat pumps
  - engine driven, 832–835
  - in process integration, 851–853
  - refrigerators, 823–829
    - evaporator systems for, 825–826
  - use in air conditioning, 829–832
  - use in liquefaction of gases, 829
  - vapour compression cycle, 820–823
- Heat transfer
  - applications in the process industries, 2–4
  - associated with thermodynamics cycles, 807–839
  - by conduction, 12–55
  - by convection, 55–119
  - by radiation, 120–150
  - definition of, 11
  - effect of fouling on, 860
  - in agitated vessels, 937–954
    - in coils, 941–945
    - in jacket (and limpet coil), 940–941
    - in vessel wall and outside coils, 945–953
  - in boiling, 423–467
  - in direct contact, 693–722
  - in direct contact condensers, 725–745
  - in falling film evaporators, 541–550
  - in film condensation, 574–590
  - in furnaces, 778–788
  - in heat exchangers, basic theory of, 155–195
  - in multicomponent condensation, 591–639
  - in plate-and-frame heat exchangers, 331–334
  - in plate-fin heat exchangers, 297–324
  - in reboilers, 504–515
  - in shell-and-tube heat exchangers, 269–285
- Heat transfer coefficient
  - definition of, 12
  - in boiling, 423–467
    - in forced convective boiling, 448–453
    - in nucleate pool boiling, 442–448
    - in postdryout region, 453–454
  - in condensation, 573–576
    - on shell-side, 660–662
  - in convective heat transfer, 55–119
  - in falling film evaporators, 541–550
  - in plate-and-frame exchangers, 331–335
  - in plate-fin heat exchangers, 297–312
  - in shell-and-tube heat exchangers, 267
    - Bell-Delaware method, 275–285
    - flow stream-analysis method, 285–292
    - Kern method, 271–275
  - typical values of, 159
- Heat transfer fluids, 231–232



Helical coils, see Coils  
 Helical coil evaporator, 560  
 Helical fire-tube waste heat boilers, 493  
 Helical ribbon agitators, for agitated vessels, 939  
 Helium,  
   gaseous, atmospheric pressure, properties of, 1019–1020  
   saturation properties of, 1012  
*n*-Heptane, saturation properties of, 987  
 Heterogeneous nucleation of bubbles, 425–428  
 Hewitt and Roberts flow pattern map (for vertical gas-liquid flow), 393  
*n*-Hexane, saturation properties of, 987  
 High-fin tubes, 87–88  
 Homogeneous condensation, 573  
 Homogeneous density, in two-phase flow, 399  
 Homogeneous nucleation of bubbles, 425  
 Homogeneous (two-phase flow) model  
   continuity equation for, 399  
   for critical mass flow, 415  
   frictional pressure gradient from  
     in flow through changes of cross section and round bends, 400–401  
     in pipe flow, 400  
   momentum equation for, 400–401  
 Horizontal fire-tube (cross-flow) waste heat boilers, 497  
 Horizontal shell-side evaporator, 557–558  
 Horizontal thermosyphon reboiler, 504–505  
   problems in design of, 515  
 Horizontal tubes  
   condensation heat transfer on inside of, 593–594  
   condensation heat transfer on outside of, 590–593  
   critical heat flux in, 464–465  
   two-phase flow in, 391–396  
 Hottel string rule, for view factor, 136  
 Humidification, application of psychrometric chart to, 759–760  
 Humidity, 751–752  
   relative, 756  
 Hydrogen  
   gaseous, atmospheric pressure, properties of, 1020  
   saturation properties of, 1013  
 Hydrogen chloride, saturation properties of, 1013  
 Hydrogen fluoride, saturation properties of, 1014  
 Hydrogen sulphide, saturation properties of, 1014

## I

Inclined tubes, two-phase flow patterns in, 394  
 Immiscible liquid condensation, 574  
 Indirect electrical resistance heating, 917–923  
   sheathed elements for, 918–922  
   unsheathed elements for, 918  
 Induced draft air-cooled heat exchangers, 366–367  
 Induced draft cooling towers, 747  
 Induction heating, 923–928  
   basic concepts, 924–926  
   power absorbed, 926  
   skin effect, 924  
   practical aspects, 926–928

Inertia, effect on film-wise condensation, 578–579  
 Infrared heating, 932–936  
 Instability, in boiling, 483–485  
   Bouré and Mihaila method for estimation of onset, 530  
   dynamic instabilities, 484–485  
     due to compressible volumes, 484  
     density wave, 484–485  
     parallel channel, 484  
   in fossil fuel fired boilers, 487  
   static (Ledinegg) instability, 483  
 Interfacial shear stress, effect of condensation on, 599–604  
 Intermittent (gas-liquid) flow, 392  
 Internal flow, heat transfer in, 98–108  
 Internal heat generation, conduction with, 36–42  
 Internal reboiler, 499  
 Irradiation, total, 131  
 Isobutane, saturation properties of, 985  
 Isopentane, saturation properties of, 986

## J

Jackets, for agitated vessels, heat transfer in, 940–941  
 Jacob number, 738  
 Jet and sheet type direct contact condenser, 726  
   theoretical models for, 734–738  
 Joule effect, for heating, 917

## K

Kern method, for heat transfer and pressure drop in shell-and-tube exchangers, 271–275  
 Kern-Seaton equation, for variation of fouling resistance with time, 858  
 Kettle reboiler, 499–501  
   heat transfer and circulation in, 506–512  
   homogeneous model for calculation of, 531–534  
   problems in design of, 515  
 Kirchhoff's Law, 132–135  
 Kosky and Staub analysis for turbulent, shear controlled film-wise condensation, 583–588

## L

Lagging, effect on heat losses from pipe, 24–26  
 Lambert's cosine law, for radiation intensity, 124  
 Lamella heat exchanger, 204  
 Laminar flow  
   developing, in a pipe, 57, 94  
   enhancement of heat transfer in, 883, 886–889  
   forced convection heat transfer in, 99–104  
     in the entrance region, 99–102  
   friction factor and pressure drop for in a pipe, 96–97  
     in fully developed flow, 103–104  
   fully developed, in a pipe, 94–97  
   in filmwise condensation  
     gravity controlled, 574–580  
     shear controlled, 580–589  
   in plate-fin heat exchangers, 306–307

- transition between laminar and turbulent flow in a pipe, 56
- Ledinegg (static) instability in boiling, 483–484
- Lewis number, 617
- Lewis relationship, 617
  - application in air-water system, 754
- Limpet coils, for agitated vessels, heat transfer in, 940–941
- Linde high flux surface, 892
- Liquefaction of gases, 829
- Liquid-gas flow, see Two-phase flow
- Liquid-liquid contactors, for direct contact heat transfer, 704
- Liquid-liquid direct contact heat transfer, 696
- Ljunstrom regenerators, see Rotary regenerators
- Lockhart and Martinelli correlations for two-phase flow
  - pressure drop, 401
  - void fraction, 413–414
- Logarithmic mean temperature difference
  - in double pipe exchanger, 239
  - in pure countercurrent flow, 166–169
  - in pure cocurrent flow, 169–170
- Long-tube vertical evaporator, 553–557
- Loss factors (dielectric) for common materials, 930
- Low-fin tubes, 85–87

## M

- McNaught equation, for condensation in cross flow over tube arrays, 661
- Maldistribution
  - in air cooled heat exchangers, 684
  - as limitation in design of vapour generators, 483
- Martinelli-Nelson correlations two-phase flow
  - for frictional pressure drop, 401
  - for void fraction, 403, 413
- Martinelli parameter (X), 403
- Mass transfer
  - in binary mixtures, 606–612
  - in multicomponent mixtures, 617
- Matrix heat exchangers, see Plate-fin heat exchangers
- Maximum heat transfer rate, in heat exchangers, 182–183
- Mean temperature difference
  - in air-cooled heat exchangers, 372–387
  - basic theory, 155–195
  - in condensation in shell-and-tube heat exchangers, 662–663
  - in cross-flow exchangers, 180–181
  - in double pipe exchangers, 239–241
  - in plate-and-frame heat exchangers, 337–338
  - in shell-and-tube exchangers, 170–179
- Mean temperature difference relationships
  - charts for shell-and-tube exchangers
    - 2-tube pass, 1-series shell, 175(F), 187, 961 (F,  $\theta$ )
    - 2-tube pass, 2-series shell, 178(F), 962 (F,  $\theta$ )
    - 2-tube pass, 3-series shell, 178(F), 963 (F,  $\theta$ )
    - 2-tube pass, 4-series shell, 179(F), 964 (F,  $\theta$ )
    - 2-tube pass, 5-series shells, 965 (F,  $\theta$ )
    - 2-tube pass, 6-series shell, 179(F), 966 (F,  $\theta$ )
    - 2-tube pass, G shell, 969 (F,  $\theta$ )
  - 1-tube pass, J shell, 967 (F,  $\theta$ )
  - 2-tube pass, J shell, 968 (F,  $\theta$ )
- cross-flow heat exchangers (with one cross-flow stream unmixed)
  - with other stream unmixed, 179(F), 188, 377 (F,  $\theta$ )
  - two pass U-tube, 179(F), 378, 975 (F,  $\theta$ )
  - one tube row, one pass, 373, 971, (F,  $\theta$ )
  - two tube rows, one pass, 374, 972 (F,  $\theta$ )
  - three tube rows, one pass, 375, 973 (F,  $\theta$ )
  - four tube rows, one pass, 376, 974 (F,  $\theta$ )
  - three tube rows, three passes, 379, 976 (F,  $\theta$ )
  - four tube rows, four passes, 380, 977 (F,  $\theta$ )
  - four tube rows, two passes, 978, (F,  $\theta$ )
- Melting points
  - of metals, 1022–1025
  - of selected substances, 983–1017
- Merkel integral, 765
- Merkel method, for prediction of cooling towers, 762–771
  - British Standard quadrature method for, 765
  - Merkel integral, 765
  - packing function, 765, 768
- Mercury, saturation properties of, 1015
- Metals
  - electrical resistivity of, 916
  - thermophysical properties of, 1022–1025
- Methane, saturation properties of, 983
- Methanol, saturation properties of, 997
- Methyl acetate, saturation properties of, 1004
- Methyl-*t*-butyl ether, saturation properties of, 1003
- Microwave heating, 928–932
  - types of applicators for, 931
  - multimode, 931
  - serpentine, 931
- Minimum energy requirements, in heat exchanger networks, 841–853
- Molecular weight, of selected substances, 983–1017
- Momentum equation (two-phase flow)
  - homogeneous model, 400–401
  - separated-flow model, 400–401
- Monochromatic absorptivity
  - directional, 132
  - hemispherical, 132
- Monochromatic emissive power, 121
- Moody chart, for pipe flow friction factor, 97
- Multicomponent boiling, 433–442
  - in pool boiling, 436–438
  - in forced convective boiling, 438–442
- Multicomponent condensation, 599–639
  - Colburn-Drew method, for binary vapour condensation in shell-and-tube heat exchangers, 619–624
  - Colburn-Hougen method, for condensation in presence of in condensable gas, 619–624
- equivalent laminar films model for, 599–603
  - effect of condensation on heat transfer between gas and interface in, 604–606
  - effect of condensation on shear stress in, 599–603
  - mass transfer effects, 606–613

Multiple effect evaporators, 565–570  
Multitubular double pipe heat exchanger, 260

## N

Natural convection heat transfer, 108–120  
  combined with radiation, 143–144  
  enhancement of, 881, 886–889  
  for upwards facing surface and three-dimensional objects, 114–115  
  from downwards facing surface, 113–114  
  from vertical flat plates, 111–113  
    laminar, 111–112  
    turbulent, 112–113  
  in cavities, 117–119  
  mechanisms of, 109  
  nondimensional numbers for, 109–111  
Natural draft cooling towers, 747–749  
Neon, saturation properties of, 1012  
Network, heat exchanger, design of using process integration, 849–851  
Nitrogen  
  gaseous, atmospheric pressure, properties of, 1020  
  saturation properties of, 1016  
Noise generation, in air-cooled heat exchangers, 684–685  
*n*-Nonane, saturation properties of, 988  
Nonproximity agitators, for agitated vessels, 939  
Normal boiling point, of selected substances, 983–1017  
NTU  
  charts for, see Mean temperature difference relationships  
  definition of, 183  
  use in direct contact heat transfer, 712–714  
Nucleate boiling  
  in cross flow boiling, 430–432  
  in evaporators, 552–558  
  in forced, convective boiling, 429–430  
  in multicomponent boiling, 433–438  
  in pool boiling, 428–429  
Nucleation, of bubbles, 423–428  
  critical radius for, 425  
  heterogeneous, 425–427  
  homogeneous, 425  
Number of transfer units, see NTU  
Nusselt number  
  definition of, 61  
  relation to equivalent laminar layer thickness, 605  
Nusselt relationships for condensation  
  on outside of horizontal tube, 590  
  in tube array, 660  
  on a vertical surface, 574–578  
    effect of interfacial waves on, 579  
    effect of sub-cooling and inertia on, 578  
    effect of turbulence on, 579–580  
    effect of vapour superheat on, 578–579

## O

*n*-Octane, saturation properties of, 988  
Overall heat transfer coefficient

  in air-cooled heat exchangers, 371  
  derivation of, 155–158  
    for cylindrical wall, 157–158  
    for flat plate, 155–157  
  in double pipe exchanger, 239  
  typical values for, 220–229  
    air-cooled heat exchangers, 229  
    double pipe exchangers, 223–225  
    gasketed plate exchangers, 226–227  
    shell-and-tube exchangers, 220–222

## Oxygen

  gaseous, atmospheric pressure, properties of, 1021  
  saturation properties of, 1016

## P

### Packed columns

  condensation in, 738–739  
  flooding in, 719–722  
  for direct contact heat transfer, 699

### Packing function, cooling towers, 765

### Packings

  in cooling tower, 765  
  pressure loss in, 772

### Pancake (flat) waste heat boiler, 493

### Parallel channel instability, in boiling, 484

### Parallel/series arrangements, in double-pipe heat exchangers, 247–253

### Particles, use in augmentation of heat transfer, 885

### Particulate fouling, 862–863

### Passive methods, for enhancement of heat transfer, 879–886

### Peclet number, 742

### *n*-Pentane, saturation properties of, 986

### Perforated plate columns, for direct contact heat transfer, 699–703

### Performance calculations, in plate-fin heat exchangers, 312–323

### Phenol, saturation properties of, 1000

### “Pinch” in process integration, 844–849

### Pinch technology, see Process integration

### Pipe lagging, effect on heat losses, 24–26

### Pipes, see Tubes

### Pipes,

  convective heat transfer in, 104–108  
  natural convection from outside of, 116–117

### Planck’s distribution law, for emissive power, 121

### Plate-and-frame heat exchangers, 327–363

  advantages and disadvantages, 329–330  
  applications of, 327–329  
  configuration of, 335–336  
  corrugation forms in, 330–331  
  description of, 201–202, 327–330  
  for condensation duty, 652–653, 687–690  
    heat transfer coefficient in, 690  
    pass arrangement for, 687–688  
    pressure drop in, 689

  heat transfer and pressure drop in, 330–335  
    inlet and outlet pressure losses, 335  
    plate heat transfer, 331–334  
    pressure losses in plate, 335

- thermal performance calculations of, 336–357
    - design for specific duty, 357
    - effectiveness in, 338
    - mean temperature difference, 337–338
    - single pass counterflow, 339–345
    - two-pass/one-pass, 347–357
    - two-pass/two-pass, 345–347
  - typical U and C values for, 224–226
  - Plate exchanger, *see* Plate-and-frame heat exchanger,
    - Welded plate exchanger, Plate-fin exchanger
  - Plate-fin heat exchangers, 297–325
    - comparison of alternative geometries, 308–310
    - for condensation duty, 653–654, 690–691
    - design procedure, 323–324
    - for evaporation duty, 557–558
    - extended surface geometries, 298
    - heat transfer and pressure drop, 298–312
      - for laminar flow, 301–307
      - for turbulent flow, 307–308
    - interrupted fin systems, 308–310
    - performance calculations, 312–323
    - structural features of, 297–298
  - “Plateau” resistance, due to fouling, 858
  - Plug flow
    - in horizontal tubes, 392
    - in vertical tubes, 391
  - Plug flow furnace model, 798–804
  - Pool boiling
    - critical heat flux in, 454–458
    - heat transfer correlations for,
      - in film boiling, 453
      - in multicomponent systems, 433–439
      - in nucleate boiling, 442–448
    - regimes in, 428–429
  - Post-dryout heat transfer, 453–454
    - in forced convection boiling, 453
    - in pool boiling, 453
  - Power generation, heat transfer in, 3
  - Prandtl number
    - definition of, 61
    - of gases, at atmospheric pressure, 1018–1021
    - of selected substances under saturation conditions, 983–1017
  - Pressure drop
    - in cooling tower packings, 772–775
    - effect of fouling on, 860–862
    - equilibrium, across curved interface, 423–425
    - in finned tube arrays, 89–93
    - in pipe flow, 96–98
    - in plain tube arrays, 79–80
    - in plate-and-frame heat exchangers, 335
    - in plate-fin exchangers, 306–308
      - in laminar flow, 306–307
      - in turbulent flow, 307–308
    - in shell and tube condensers, 673
    - in shell-and-tube heat exchangers, 269–295
    - in two-phase, gas-liquid flow, 401–413
      - in changes of cross section and around bends, 401–402, 410–412
      - in shell-and-tube heat exchangers, 412–413
      - in tubes, 401, 403–406
  - Pressure drop multipliers, for two phase flow, definition of, 403
  - Process change, in process integration, 854
  - Process gas heated waste heat boilers, 492–498
    - bayonet tube boilers, 493
    - double quench tube boilers, 493
    - “flat pancake” type, 493
    - helical fire tube type, 493
    - horizontal fire tube (cross flow) type, 497
    - thin-tube-sheet type, 497
    - U-tube type, 493–494
    - vertical calandria type, 492–493
  - Process heaters, 777
    - central tube wall double fired, 779
    - horizontal tube “cabin” heater, 778
    - vertical cylindrical, 778
  - Process industries
    - applications of heat transfer in, 2–4
      - in air conditioning and space heating, 4
      - with biological reactions, 2
      - with chemical reactions, 2
    - in power generation, 3
      - with physical changes, 3
    - in waste heat recovery, 4
    - energy utilisation in, 1–3
  - Process integration, 841–855
    - composite curves, 841–849
      - minimum energy requirements, 843
      - the “pinch”, 844, 848
    - heat engines and heat pumps in, 851–853
    - heat exchanger network design, 849–851
      - stream splitting and mixing, 850–851
    - limitations of, 854
    - process change, 854
  - Propane, saturation properties of, 980
    - 1-Propanol, saturation properties of, 994
    - 2-Propanol, saturation properties of, 998
  - Propeller agitators, for agitated vessels, 939
  - Propylene, saturation properties of, 995
  - Propylene oxide, saturation properties of, 1000
  - Proximity agitators, for agitated vessels, 939
  - Psychrometric chart, 756–762
    - application to dryers, 757–759
    - application to humidification, 761–762
    - application to mixing of streams, 759–760
  - Psychrometric ratio, 755
  - Pumped reboiler, 516
  - Pure cocurrent flow heat exchanger, 169–170
    - logarithmic mean temperature difference in, 169–170
  - Pure counterflow heat exchanger, 167–169
    - logarithmic mean temperature difference in, 168–169
- ## Q
- Quality (in two-phase flow), definition of, 396
- ## R
- Radiation, 120–150
    - between reflecting surfaces, 141–143

- between surfaces, view factor, 135–141
  - blackbody radiation, 120–126
  - combined with natural convection, 143–144
  - from real surfaces, 126–131
  - in gases, 144–150
  - to real surfaces, 131–135
  - Radiative heat transfer, *see* Radiation
  - Radiofrequency heating, 928–932
    - equipment selection for, 932
    - types of applicators for, 931–932
      - heating platen, 931
      - staggered through field, 932
      - stray field electrode, 932
  - Radiosity, 136
  - Rankine cycle, 818–820
  - Rating
    - of air-cooled heat exchangers, 371–387
    - of shell-and-tube heat exchangers, 292–295
  - Reboilers, 499–535
    - horizontal thermosyphon type, 504–505
      - problems in design of, 515
      - instability in, 530–531
      - Bouré and Mihaila method, 530–531
    - internal type, 499
    - kettle type, 499–501
      - heat transfer and circulation in, 507–512
      - homogeneous method for calculation of, 531–534
      - problems in design of, 515
    - vertical thermosyphon type, 501–504
      - heat transfer and circulation in, 512–515
      - homogeneous method for calculation of, 531–534
      - nozzle arrangements for, 502
      - problems in design of, 515
      - pumped reboilers, 516
      - rating calculation for, 515–526
      - selection between types, 505–506
  - Reciprocity relationship, for radiation view factor, 140
  - Recuperative heat exchangers, definition, 4
  - Reduced lengths, in regenerative heat exchanger design, 900
  - Reflecting surfaces, radiation between, 141–143
  - Reflux condensers, 646
    - air-cooled, 679
    - flooding in, 416–418
  - Refrigerant 12, saturation properties of, 1000
  - Refrigerant 13, saturation properties of, 1001
  - Refrigerant 21, saturation properties of, 1001
  - Refrigerant 22, saturation properties of, 1002
  - Refrigerators
    - absorption cycle, 835–837
    - vapour compression cycle, 823–829
  - Regenerative heat exchangers, 895–913
    - cyclic (fixed bed) regenerators
      - calculation of, 905–906
      - description of, 212, 895–897
    - definition, 4
    - design of, 897–912
      - effects of geometry, 908
      - effects of material thermal conductivity, 909–912
      - parameters for, 900
      - symmetric counterflow system, 901–905
      - theoretical model for, 897–900
    - rotary regenerators
      - calculation of, 905–906
      - description of, 212–213, 896–897
  - Regenerators
    - for gas turbine systems, 811–814
    - in liquefaction of gases, 829
  - Relative humidity, 756
  - Resistance, due to fouling, *see* Fouling
  - Resistance heating (electrical), 915–923
    - basic theory of, 916–917
    - direct heating, 923
    - indirect heating, 917–923
      - sheathed elements, 918–922
      - unsheathed elements, 918
  - Resistivity, electrical, of metals, 917
  - Reynolds analogy, 62–63
  - Reynolds number, definition of
    - for a flat plate, 64
    - for a pipe, 56
  - Rib roughness, effect on heat transfer, 882
  - Rohsenow correlation, for nucleate boiling, 444
  - Rotary regenerators, 212–213, 896–897
    - calculation of, 905–906
  - Rough surfaces, for enhancement of heat transfer, 881
- ## S
- Saturation pressure/temperature data of selected substances, 983–1017
  - Schlunder method, for multicomponent boiling, 438
  - Schmidt correlation, for in-line arrays of high-fin tubes, 88
  - Scraped surface heat exchangers, 215, 886–889
  - Seider-Tate equation, 106
  - Selection of heat exchangers, 197–232
    - for condensation duty, 644–646
    - for evaporation duty, 565
    - initial selection, 215
    - for reboiling duty, 505–506
    - survey of available types, 198–215
    - selection between feasible types, 215–231
      - C-value method, 215–231
  - Semiinfinite solids, transient conduction in, 44–47
    - with harmonically varying surface temperature, 44–47
    - with sudden increase in surface temperature, 44
  - Separated flow model (two-phase flow)
    - continuity equation for, 400
    - frictional pressure gradient in tubes from, 403–406
    - momentum equation for, 400–401
    - pressure drop in changes of cross section and bends from, 410
  - Shape factor, in two-dimensional conduction, 34–36
  - Shear controlled filmwise condensation, 580–589
    - in horizontal tubes, 593–595
  - Shear stress, effect on fouling, 866
  - Sheathed elements, for indirect electrical resistance heating, 918–922
  - Shell-and-tube heat exchangers, 263–296
    - for condensation duty, 646–650

- condensation of multicomponent mixtures in, 668–673
- desuperheating and subcooling in, 663–668
- horizontal tube-side, 646
- horizontal shell-side, E-shell, 647
- horizontal shell-side, J-shell, 647
- horizontal shell-side, rod baffled, 649
- mean temperature difference in, 662–663
- mixtures in, 668–673
- pressure drop in, 673
- shell-side heat transfer in, 660–662
- vertical reflux, in-tube, 646
- vertical shell-side, 646
- vertical tube-side, 646
- description of, 198–200
- design process for, 263–265
- heat transfer and pressure drop calculations for, 269–295
  - Bell-Delaware method, 275–285
  - flow-stream analysis method, 285–292
  - Kern method, 271–275
- mean temperature difference in, 170–179
  - multiple shells, 176–177
  - two-pass exchanger, 170–176
- mechanical features of, 265–269
  - baffles, 267–269
  - shell types, 265
  - tube bundles, 265–267
- rating and design of, 292–295
- two-phase flow patterns in, 394–396
- two-phase pressure drop in, 412–413
- typical overall coefficient and C-values for, 218–220
- Sherwood number
  - definition of, 61–62
  - relation to equivalent laminar layer thickness, 616
- Short-tube vertical evaporator, 552
- Silver-Bell-Ghaly method for approximate design of multicomponent condensers, 635–639
  - application to multipass shell and tube heat exchangers, 668–673
- Skin effect, in induction heating, 920
- Slab, thick, transient conduction in, 49–55
- Slip ratio, in two-phase flow, definition of, 397
- Slug flow
  - in horizontal tubes, 392
  - in vertical tubes, 391
- Soil, transient conduction in, with sinusoidally varying interface temperature, 46–47
- Solid-fluid contactors, for direct contact heat transfer, 704–706
- Solid-fluid direct contact heat transfer, 696
- Space heating, heat transfer in, 4
- Specific heat capacity, of selected substances under saturation conditions, 983–1017
  - of metals, 1022–1025
- Spheres
  - general equations for conduction in, 18
  - steady state conduction in, 23–24
- Spiral exchanger, 203–204
  - for evaporation duty, 557–558
- Spiral plate evaporator, 558
- Spray columns for direct contact heat transfer, 699
  - fluid dynamics of, 717–718
- Stanton number, 616
- Static (Ledinegg) instability in boiling, 483–484
- Steam generators, 487–498
  - fossil fuel fired boilers, 487–491
    - circulation rate in, 488
    - dryout in, 488
    - fire-tube type, 487
    - instability in, 488
    - steam separation in, 488
    - water quality control in, 488
    - water-tube type, 487
  - waste heat boilers, 491–498
    - flue gas heated types, 491–492
    - process gas heated boilers, 492–498
- Steam separation, in fossil fuel fired boilers, 488
- Steam turbines, 818–820
  - Rankine cycle for, 818–820
- Stefan-Boltzmann constant, 122
- Stefan-Boltzmann law, for emissive power, 122
- Stephan and Korner method, for multicomponent boiling, 436–437
- Stratified flow
  - in cross-flow over tube banks, 397
  - in horizontal tubes, 391
- Stratified wavy flow, 392
- Stream analysis method, for shell-and-tube heat exchangers, 285–292
- Stream mixing, in process integration, 850–851
- Subcooling, effect on filmwise condensation, 578
- Sudden enlargement, see Enlargement, sudden
- Summation rule, for radiation in cavities, 140–141
- Superheat, vapour, effect on condensation, 578–579
- Surface tension, of selected substances under saturation conditions, 983–1017
- Surface treatment, for enhancement of heat transfer, 881
- Swirl flow, for enhancement of heat transfer, 881
- Symmetric counterflow regenerators, 901–905

## T

- Taitel and Dukler flow pattern map (for horizontal gas-liquid flow), 395
- TEMA standards for shell-and-tube heat exchangers, 265–269
- Temperature profiles
  - in heat exchangers, 162–164
  - in shell-and-tube condensers condensing multicomponent mixtures, 668–673
  - in vapour generators, 479–481
- Thermal conductivity, 13–16
  - of gases, at atmospheric pressure, 1018–1021
  - of metals, 1022–1025
  - of selected substances under saturation conditions, 983–1017
- Thermal diffusivity, 44
  - of gases, at atmospheric pressure, 1018–1021
  - of metals, 1022–1025
- Thermal effectiveness, 183
  - in regenerative heat exchangers, 905

- Thermal expansion coefficient, for selected substances under saturation conditions, 983–1017
- Thermal radiation, *see* Radiation
- Thermal resistance, general expression for, 26–27
- Thermodynamic cycles, heat transfer associated with, 807–839
  - absorption cycles, 835–838
    - Electrolux refrigeration cycle, 837–838
    - simple absorption cycle refrigerator, 835–837
  - heat engines, 807, 811–820
    - gas turbines, 811–818
    - steam turbines, 818–820
  - heat pumps, 807, 820–835
    - air conditioning duty, 829–831
    - engine driven, 832–835
    - heating by, 829–835
    - liquefaction of gases by recycling, 829
    - refrigerators, 823–829
    - vapour compression cycle, 820–823
- Thermosyphon reboilers
  - horizontal, 504–505
    - problems in design of, 515
  - vertical, 501–504
    - heat transfer and circulation in, 512–515
    - homogeneous method for calculation of, 531–532
    - nozzle arrangement for, 512
    - problems in design of, 515
    - rating calculation for, 517–526
- Theta ( $\theta$ )
  - charts for, *see* Mean temperature difference relationships
  - definition of, 183–184
  - table of equations for, 956
- Thome method, for multicomponent boiling, 436
- Toluene, saturation properties of, 991
- Total absorptivity, 132
- Total emissive power, 122, 125
- Total irradiation, 131
- Transient conduction, 42–55
  - diffusion of heat in, 42–43
    - thermal diffusivity, 44
  - in semiinfinite solids, 44–47
    - with harmonically varying surface temperature, 44–47
    - with sudden increase of surface temperature, 44
  - in thick slab with convection on one side and insulated on other, 49–51
  - in thick slab with radiation on one side and insulated on other, 51–55
  - with convection and radiation, 47–55
    - Biot number, 47
    - lumped parameter model, 49
- Transmural heat exchangers, 5
- Tube arrays
  - condensation in, 659–660
    - McNaught equation for, 661
    - Nusselt equation for, 660
  - finned, heat transfer in, 82–89
    - geometrical factors, 82–84
    - high-fin tubes, 87–88
    - low-fin tubes, 85–87
    - finned, pressure drop in, 89–93
    - plain, heat transfer in, 73–79
      - ESDU correlation for, 73–79
    - plain, pressure drop in, 79–80
    - two-phase flow patterns in, 397
    - two-phase pressure drop in flow over, 412–413
- Tube banks, *see* Tube arrays
- Tubes
  - boiling heat transfer in, 429–442
  - condensation heat transfer on outside of, 590–593
    - horizontal, 593–595
  - heat transfer in, 94–108
  - pressure drop in, 96–98
  - two-phase flow patterns in, 391–394
    - in horizontal tubes, 391–393
    - in inclined tubes, 394
    - in vertical tubes, 391
- Tubular Exchanger Manufacturers Association, *see* TEMA
- Turbine agitators, for agitated vessels, 939
- Turbulent bursts, effect on fouling, 859
- Turbulent flow
  - developing, in a pipe, 57
  - enhancement of heat transfer in, 883
  - friction factor for, in pipe flow, 97–98
  - in condensing falling films, 579
  - in plate-fin heat exchangers, 307–308
  - in shear controlled condensation, 580–588
  - internal heat transfer in, 104–108
    - in entrance length, 104–105
    - in fully developed flow, 105–108
  - transition between laminar and turbulent flow in a pipe, 56
- Twisted tapes, for enhancement of heat transfer, 884, 892
- Two-phase density, definition of, 397
- Two-phase (gas-liquid) flow, 391–420
  - basic equations for, 396–401
    - homogeneous model, 399–400
    - separated flow model, 400–401
  - critical mass flux in, 416–417
  - flooding in, 417–420
  - flow patterns in, 391–396
    - in cross-flow, 394–396
    - in horizontal tubes, 391–394
    - in inclined tubes, 394
    - in vertical tubes, 391
  - pressure drop in, 401–409
    - in changes of cross section and bends, 401, 410–412
    - in cross-flow, 412–413
    - in shell-and-tube heat exchangers, 412–413
    - in tubes, 401, 403–410
  - void fraction in, 413–416

## U

- Unsheathed elements, for indirect electrical resistance heating, 918
- U-tube waste heat boilers, 493–494

## V

- Vapour generators, 469–485
  - basic design of, 479–481
  - classification of, 469–479
    - according to function, 469–470
    - according to geometry, 475
    - according to heat source, 474–475
    - according to mode of heat transfer, 470–474
  - limiting factors in design of, 481–485
    - counterflow flooding, 482–483
    - dryout and critical heat flux, 482
    - instability, 483–485
    - maldistribution, 483
  - temperature profiles in, 479
- Vapour-liquid equilibrium
  - calculation of multicomponent
    - bubble point, 613
    - dew point, 613
    - equilibria, 613–615
  - for multicomponent systems, 434–436
    - Azeotrope formation, 435
  - for single component fluid, 423–425
    - for curved interface, 423
    - for planar interface, 423–424
- Vertical calandria waste heat boilers, 492
- Vertical thermosyphon reboiler, 501–504
  - heat transfer and circulation in, 512–515
  - homogeneous method for calculation of, 531–532
  - nozzle arrangement for, 513
  - problems in design of, 515
  - rating calculation for, 515–526
- Vertical tube
  - evaporators,
    - long tube, 553–554
    - short tube, 552
  - two-phase flow patterns in, 391
- Vibration, surface, in enhancement of heat transfer, 889
- View factor, in radiation
  - definition of, 135
  - Hottel string rule for, 136
  - in cavities, 137–139
  - reciprocity relation for, 136
- Viscosity
  - of gases, at atmospheric pressure, 1018–1021
  - of selected substances under saturation conditions, 983–1017
- VLE, see Vapour-liquid equilibrium
- Void fraction
  - definition of, 396
  - in cross-flow, 527
  - Lockhart and Martinelli correlation for, 404, 413
  - Martinelli-Nelson correlation for, 402, 413

## W

- Wallis correlation, for flooding in two-phase gas-liquid countercurrent flow, 418
- Waste heat boilers, 491–498
  - flue gas heated types, 491–492
    - horizontal tube boilers, 491–492
    - water tube boilers, 491
  - for gas turbine systems, 813–814
  - process gas heated types, 492–498
    - bayonet tube boilers, 493
    - double tube quench boiler, 493
    - “flat pancake” type, 493
    - helical fire tube type, 493
    - horizontal fire tube (cross flow) boiler, 497
    - thin-tube-sheet type, 497
    - U-tube type, 493–494, 496
    - vertical calandria type, 492–493
- Waste heat recovery, heat transfer in, 4
  - in gas turbine cycle, 813–814
- Water
  - gaseous, atmospheric pressure, properties of, 1021
  - saturation properties of, 1014
- Water cooling towers, see Cooling towers
- Water quality control, in fossil fuel fired boilers, 488
- Water tube boilers, 487–490
  - flue gas heated, 491–492
  - fossil fuel heated, 487
- Waves, interfacial, effect on condensation, 579
- Welded plate heat exchanger, 205
- Well-stirred furnace model, 789–798
- Wet bulb temperature, 752–756
- Wet wall desuperheating, in condensers, 664–668
  - Bell’s approximate method for, 666–668
  - detailed calculation, 664–666
- Wills and Johnson method for pressure drop and heat transfer in shell-and-tube heat exchangers, 285–292
- Wire wound tubular inserts, for heat transfer enhancement, 880
- Wispy annular flow, 391

## X

- m*-Xylene, saturation properties of, 991
- o*-Xylene, saturation properties of, 992
- p*-Xylene, saturation properties of, 992

## Z

- Zuber theory, for critical heat flux in pool boiling, 454–455