

---

# INDEX

- Air moving devices, 41
- Blowers
  - backward curve, 43
  - blade design, 43
  - centrifugal, 42
  - forward curve, 44
  - performance (P vs. Q) curve, single, 50
  - performance curves, multiple speeds, 50
  - radial, 43
- Datacenter environment, 15
- DIMM
  - power, 7
  - temperature specification, 17
- Efficiency
  - fan or blower, 47
- Fans
  - blade design, 45
  - counter rotating, 46
  - knee, 51
  - laws, 48
  - performance curve, single, 51
  - performance curve, multiple, 52
  - performance curve, multiple speeds, 51
- Heat sink, 26, 33
  - fin heat transfer, 33
  - fin efficiency, 35
  - foam, 68
  - heat pipe, 66
  - structure, 74
  - nanostructures, 66
  - vapor chamber, 63
- Impedance
  - airflow, 53
  - curve, 53
- Operating point
  - system, 54
  - multiple speeds, 54
- Pressure
  - dynamic, 47
  - head, 47
  - interface, 30
  - static, 47
  - total, 47
- Processor
  - heat flux, 6, 12
  - multi-core, 4, 18
  - package, 20
  - power, 4, 7, 13
  - power map, 19
  - thermal design power, 17
  - transistor density, 3
- Resistance
  - contact, 27
  - convective, 33, 34, 60, 61
  - thermal, 21, 36
  - junction to board, 24
  - junction to case, 22
  - junction to air, 26
  - spreading, 33, 62, 63, 67
- Thermal interface material, 20, 57
  - TIM1, 20, 30
  - TIM2, 26
  - liquid metal, 58
  - nanotechnology, 59